TOP PLATE FITTING

250 UIY

Medium Duty Institutional Castor **SERIES** 110 - 150 KGS

Castor

250 (American Specification)
Bracket made of pressed steel. Double ballrace swivel head
Metal parts: Zinc plated

Wheel

UIY (Grey, non-marking)
Made of Polyurethane HI-TECH mechanically bonded to Polyolefin core
Rolling Quietly, Abrasive, Impact, water & chemical resistance
Hardness: 95± shore A
Temperature range -20ºC to +80ºC

	mm	mm	mm	mm	mm	mm	mm	mm	mm		kgs
251 UIY 075 P01	92x64	71-78x45	8.5	105	68	075	32	9.8	38.5		110
251 UIY 100 P01	92x64	71-78x45	8.5	131	82	100	32	9.8	38.5		125
251 UIY 125 P01	92x64	71-78x45	8.5	157	98	125	32	9.8	38.5		150

252 UIY 075 P01	92x64	71-78x45	8.5	105	Rigid	075	32	9.8	38.5		110
252 UIY 100 P01	92x64	71-78x45	8.5	131	Rigid	100	32	9.8	38.5		125
252 UIY 125 P01	92x64	71-78x45	8.5	157	Rigid	125	32	9.8	38.5		150

253 UIY 075 P01	92x64	71-78x45	8.5	105	68	075	32	9.8	38.5		110
253 UIY 100 P01	92x64	71-78x45	8.5	131	82	100	32	9.8	38.5		125
253 UIY 125 P01	92x64	71-78x45	8.5	157	98	125	32	9.8	38.5		150

256 UIY 075 P01	92x64	71-78x45	8.5	105	68	075	32	9.8	38.5		110
256 UIY 100 P01	92x64	71-78x45	8.5	131	82	100	32	9.8	38.5		125
256 UIY 125 P01	92x64	71-78x45	8.5	157	98	125	32	9.8	38.5		150

	mm	mm	mm	mm		kgs
UIY 075	075	32	9.8	38.5		110
UIY 100	100	32	9.8	38.5		125
UIY 125	125	32	9.8	38.5		150