

INSTITUTIONAL MEDIUM - DUTY



260 NBZ SERIES

70 ~ 120 KGS

In compliance to Korean Standard Specification



266 Metal Total Brake

Castor 260

Armor steel, double ballrace swivel path frame
heat treatment. Finish: Black lacquer
40 Rig thickness: 2mm • Plate thickness: 2mm
50 Rig thickness: 2.5mm • Plate thickness: 2.5mm
65 Rig thickness: 2.8mm • Plate thickness: 3.5mm

Wheel NBZ

Solid Nylon, double precision ballbearing (no threadguards).
Black non-marking. Quiet rolling, abrasive, impact, water and
chemical resistance. Hardness: 60D • Temperature: -30°C to +100°C



Swivel	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	bearing	kg
261 NBZ 040 P60	71x52	53x35	8.3	63	20	41	28	6	30		70	
261 NBZ 050 P70	71x52	53x35	8.3	73	22	50	28	6	30		100	
261 NBZ 065 P01	80x58	63x40	8.3	90	30	65	28	10.1	30		120	



Rigid	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	bearing	kg
262 NBZ 040 P60	71x52	53x35	8.3	63	Rigid	41	28	6	30		70	
262 NBZ 050 P70	71x52	53x35	8.3	73	Rigid	50	28	6	30		100	
262 NBZ 065 P01	80x58	63x40	8.3	90	Rigid	65	28	10.1	30		120	



Total-Brake	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	bearing	kg
266 NBZ 040 P60	71x52	53x35	8.3	63	20	41	28	6	30		70	
266 NBZ 050 P70	71x52	53x35	8.3	73	22	50	28	6	30		100	
266 NBZ 065 P01	80x58	63x40	8.3	90	30	65	28	10.1	30		120	