

TOP PLATE FITTING 260 TPY

Medium Duty Institutional Castor **SERIES**
80 - 125 KGS

Castor

260 (American specification)
Armor steel, double ballrace swivel path frame heat treatment
Metal finish: Black lacquer

Wheel

TPY
Hardness 75± shore A (TPR Grey, non-marking)
Thermoplastic rubber, PP core single precision ball bearing (with plastic threadguard)
Temperature range: -20°C to + 80°C



	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
	261 TPY 075 P01	92x65	73x45	8.3	119	34	75	32	10.1	40		80	
	261 TPY 100 P01	92x65	73x45	8.3	133	32.5	100	32	10.1	40		110	
	261 TPY 125 P01	92x65	73x45	8.3	157	32.5	125	32	10.1	40		115	
	261 TPY 150 P01	92x65	73x45	8.3	185	45	150	32	10.1	40		125	
	262 TPY 075 P01	92x65	73x45	8.3	119	34	75	32	10.1	40		80	
	262 TPY 100 P01	92x65	73x45	8.3	133	32.5	100	32	10.1	40		110	
	262 TPY 125 P01	92x65	73x45	8.3	157	32.5	125	32	10.1	40		115	
	262 TPY 150 P01	92x65	73x45	8.3	185	45	150	32	10.1	40		125	
	263 TPY 075 P01	92x65	73x45	8.3	119	34	75	32	10.1	40		80	
	263 TPY 100 P01	92x65	73x45	8.3	133	32.5	100	32	10.1	40		110	
	263 TPY 125 P01	92x65	73x45	8.3	157	32.5	125	32	10.1	40		115	
	263 TPY 150 P01	92x65	73x45	8.3	185	45	150	32	10.1	40		125	
	264 TPY 075 P01	92x65	73x45	8.3	119	34	75	32	10.1	40		80	
	264 TPY 100 P01	92x65	73x45	8.3	133	32.5	100	32	10.1	40		110	
	264 TPY 125 P01	92x65	73x45	8.3	157	32.5	125	32	10.1	40		115	
	264 TPY 150 P01	92x65	73x45	8.3	185	45	150	32	10.1	40		125	
	266 TPY 075 P01	92x65	73x45	8.3	119	34	75	32	10.1	40		80	
	266 TPY 100 P01	92x65	73x45	8.3	133	32.5	100	32	10.1	40		110	
	266 TPY 125 P01	92x65	73x45	8.3	157	32.5	125	32	10.1	40		115	
	266 TPY 150 P01	92x65	73x45	8.3	185	45	150	32	10.1	40		125	