

# THREADED STEM FITTING

## 260 TPY

Medium Duty Institutional Castor **SERIES**  
80 - 125 KGS



### Castor

**260** (American specification)  
Armor steel, double ballrace swivel path frame heat treatment  
Metal finish: Black lacquer

### Wheel

**TPY**  
Hardness 75± Shore A (TPR Grey, non-marking)  
Thermoplastic rubber, PP core single precision ball bearing (with plastic threadguard)  
Temperature range: -20°C to + 80°C



	mm	mm	mm	mm	mm	mm	mm	mm	mm	daN	kgs
<b>261 TPY 075 T12</b>	M12	30	119	34	75	32	10.1	40	—	80	80
<b>261 TPY 100 T12</b>	M12	30	133	32.5	100	32	10.1	40	—	110	110
<b>261 TPY 125 T12</b>	M12	30	157	32.5	125	32	10.1	40	—	115	115
<b>261 TPY 150 T12</b>	M12	30	185	45	150	32	10.1	40	—	125	125

Threaded stem 5/8" - 11 UNC x30mm also available (Suffix T06)  
Option: Other fitting available on request.



<b>263 TPY 075 T12</b>	M12	30	119	34	75	32	10.1	40	—	80	80
<b>263 TPY 100 T12</b>	M12	30	133	32.5	100	32	10.1	40	—	110	110
<b>263 TPY 125 T12</b>	M12	30	157	32.5	125	32	10.1	40	—	115	115
<b>263 TPY 150 T12</b>	M12	30	185	45	150	32	10.1	40	—	125	125

Threaded stem 5/8" - 11 UNC x30mm also available (Suffix T06)  
Option: Other fitting available on request.



<b>264 TPY 075 T12</b>	M12	30	119	34	75	32	10.1	40	—	80	80
<b>264 TPY 100 T12</b>	M12	30	133	32.5	100	32	10.1	40	—	110	110
<b>264 TPY 125 T12</b>	M12	30	157	32.5	125	32	10.1	40	—	115	115
<b>264 TPY 150 T12</b>	M12	30	185	45	150	32	10.1	40	—	125	125

Threaded stem 5/8" - 11 UNC x30mm also available (Suffix T06)  
Option: Other fitting available on request.



<b>266 TPY 075 T12</b>	10.3	12.8	119	34	75	32	10.1	40	—	80	80
<b>266 TPY 100 T12</b>	10.3	12.8	133	32.5	100	32	10.1	40	—	110	110
<b>266 TPY 125 T12</b>	10.3	12.8	157	32.5	125	32	10.1	40	—	115	115
<b>266 TPY 150 T12</b>	10.3	12.8	185	45	150	32	10.1	40	—	125	125