

TOP PLATE FITTING 260 URY/URA

Medium Duty Institutional Castor **SERIES 60 - 165 KGS**



Castor 260 (American specification)
Armor steel, double ballrace swivel path frame heat treatment
Metal Finish: Black lacquer

Wheel URA Hardness 94± Shore A (PU Red, non-marking)
Polyurethane, PP core plain bearing (without threadguards)
Temperature range: -20°C to +90°C

URY Hardness 94± Shore A (PU Red, non-marking)
Polyurethane, PP core single precision ball bearing (with plastic threadguards)
Temperature range: -20°C to +90°C



	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	daN	kg
201 URA 063 P70	70x60	53x42	8.3	86	24	63	30	8.1	35	—	—	60	
261 URY 075 P01	92x65	73x45	8.3	119	34	75	32	10.1	40	●	●	110	
261 URY 100 P01	92x65	73x45	8.3	133	32.5	100	32	10.1	40	●	●	125	
261 URY 125 P01	92x65	73x45	8.3	157	32.5	125	32	10.1	40	●	●	150	
261 URY 150 P01	92x65	73x45	8.3	185	45	150	32	10.1	40	●	●	165	
202 URA 063 P70	70x60	53x42	8.3	86	24	63	30	8.1	35	—	—	60	
262 URY 075 P01	92x65	73x45	8.3	119	34	75	32	10.1	40	●	●	110	
262 URY 100 P01	92x65	73x45	8.3	133	32.5	100	32	10.1	40	●	●	125	
262 URY 125 P01	92x65	73x45	8.3	157	32.5	125	32	10.1	40	●	●	150	
262 URY 150 P01	92x65	73x45	8.3	185	45	150	32	10.1	40	●	●	165	
263 URY 075 P01	92x65	73x45	8.3	119	34	75	32	10.1	40	●	●	110	
263 URY 100 P01	92x65	73x45	8.3	133	32.5	100	32	10.1	40	●	●	125	
263 URY 125 P01	92x65	73x45	8.3	157	32.5	125	32	10.1	40	●	●	150	
263 URY 150 P01	92x65	73x45	8.3	185	45	150	32	10.1	40	●	●	165	
204 URY 063 P01	70x60	53x42	8.3	86	24	63	30	8.1	35	—	—	60	
264 URY 075 P01	92x65	73x45	8.3	119	34	75	32	10.1	40	●	●	110	
264 URY 100 P01	92x65	73x45	8.3	133	32.5	100	32	10.1	40	●	●	125	
264 URY 125 P01	92x65	73x45	8.3	157	32.5	125	32	10.1	40	●	●	150	
264 URY 150 P01	92x65	73x45	8.3	185	45	150	32	10.1	40	●	●	165	
266 URY 075 P01	92x65	73x45	8.3	119	34	75	32	10.1	40	●	●	110	
266 URY 100 P01	92x65	73x45	8.3	133	32.5	100	32	10.1	40	●	●	125	
266 URY 125 P01	92x65	73x45	8.3	157	32.5	125	32	10.1	40	●	●	150	
266 URY 150 P01	92x65	73x45	8.3	185	45	150	32	10.1	40	●	●	165	