

TOP PLATE / THREADED STEM

290 NMH

Medium-Heavy Duty Castor **SERIES**
260 - 380 KGS



Option: Other colour On Request

Castor

290 (American specification)
Armor steel, double reverse ballrace swivel path frame heat treatment.
Metal finish: Black lacquer

Wheel

NMH
Polyamide nylon-6 (Nylon black non-marking, PP core white)
Nylon-6, PP core double precision ball bearing (without threadguards)
Temperature range: -30°C to +100°C

	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	daN	kgs
	291 NMH 100 P45	113x100	84x74	11	136	42	100	40	12	51.5	***	***	260	
	291 NMH 125 P45	113x100	84x74	11	163	42	125	40	12	51.5	***	***	350	
	291 NMH 150 P45	113x100	84x74	11	190	42	150	40	12	51.5	***	***	380	
	292 NMH 100 P45	113x100	84x74	11	136	Rigid	100	40	12	51.5	***	***	260	
	292 NMH 125 P45	113x100	84x74	11	163	Rigid	125	40	12	51.5	***	***	350	
	292 NMH 150 P45	113x100	84x74	11	190	Rigid	150	40	12	51.5	***	***	380	
	296 NMH 100 P45	113x100	84x74	11	136	42	100	40	12	51.5	***	***	260	
	296 NMH 125 P45	113x100	84x74	11	163	42	125	40	12	51.5	***	***	350	
	296 NMH 150 P45	113x100	84x74	11	190	42	150	40	12	51.5	***	***	380	
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	daN	kgs	
	291 NMH 100 T16	M16	30	136	42	100	40	12	51.5	***	***	260		
	291 NMH 125 T16	M16	30	163	42	125	40	12	51.5	***	***	350		
	291 NMH 150 T16	M16	30	190	42	150	40	12	51.5	***	***	380		
	296 NMH 100 T16	M16	30	136	42	100	40	12	51.5	***	***	260		
	296 NMH 125 T16	M16	30	163	42	125	40	12	51.5	***	***	350		
	296 NMH 150 T16	M16	30	190	42	150	40	12	51.5	***	***	380		