TOP PLATE / THREADED STEM

290 UMH

Medium-Heavy Duty Castor **SERIES** 170 - 235 KGS

Option: Other colour on request

Castor

290 (American specification)
Armor steel, double/reverse ballrace swivel path frame heat treatment
Metal Finish: Black lacquer

Wheel

UMH Hardness 94± Shore A (PU Yellow, non-marking, PP core black)
Polyurethane, PP core double precision ball bearing (without threadguards)
Temperature range: -20°C to +90°C

	mm	mm	mm	mm	mm	mm	mm	mm	mm		daN
											kgs
291 UMH 100 P45	113x100	84x74	11	136	42	100	40	12	51.5		170
291 UMH 125 P45	113x100	84x74	11	163	42	125	40	12	51.5		205
291 UMH 150 P45	113x100	84x74	11	190	42	150	40	12	51.5		235

292 UMH 100 P45	113x100	84x74	11	136	RIGID	100	40	12	51.5		170
292 UMH 125 P45	113x100	84x74	11	163	RIGID	125	40	12	51.5		205
292 UMH 150 P45	113x100	84x74	11	190	RIGID	150	40	12	51.5		235

296 UMH 100 P45	113x100	84x74	11	136	42	100	40	12	51.5		170
296 UMH 125 P45	113x100	84x74	11	163	42	125	40	12	51.5		205
296 UMH 150 P45	113x100	84x74	11	190	42	150	40	12	51.5		235

	mm	mm	mm	mm	mm	mm	mm	mm		daN
										kgs
291 UMH 100 T16	M16	30	136	42	100	40	12	51.5		170
291 UMH 125 T16	M16	30	163	42	125	40	12	51.5		205
291 UMH 150 T16	M16	30	190	42	150	40	12	51.5		235

296 UMH 100 T16	M16	30	136	42	100	40	12	51.5		170
296 UMH 125 T16	M16	30	163	42	125	40	12	51.5		205
296 UMH 150 T16	M16	30	190	42	150	40	12	51.5		235