



Impact Bit Socket

KT No. & D1



3065M

3/8"

- For hexagon head screw
- DIN 3121



KT NO.	mm	L mm	Max. torq Nm		
306504M	H4	90	20.8	42	8 / 160
306505M	H5	90	36.0	48	8 / 160
306506M	H6	90	62.4	55	8 / 160
306508M	H8	90	144.0	73	8 / 160
306510M	H10	90	264.0	96	8 / 160

3053M

3/8"

- For torx internal screw
- DIN 3121



KT NO.	Size	L mm		
305310	T10	55	30	12 / 360
305315	T15	55	30	12 / 360
305320	T20	55	32	12 / 360
305325	T25	55	32	12 / 360
305327	T27	55	33	12 / 360
305330	T30	55	34	12 / 360
305340	T40	55	37	12 / 360
305345	T45	55	41	12 / 360
305350	T50	55	44	12 / 360
305355	T55	55	58	12 / 288
305360	T60	55	65	12 / 288

Impact Accessory

3862P

3/8"

- Adapter
- Convert to 1/4" drive
- 3862P → Max. torque : 62 Nm
- DIN 3121



KT NO.	Spec.	D mm		
3862P	3/8"F x 1/4"M	20.8	33	24 / 384

3864P

3/8"

- Adapter
- Convert to 1/2" drive
- DIN 3121



KT NO.	Spec.	D mm		
3864P	3/8"F x 1/2"M	20.8	51	24 / 384

3147

3/8"

- Bit holder



KT NO.	Size	L mm		
314708S	1/4"	40	44	12 / 420
314710S	5/16"	40	45	12 / 420
314710M	10mm	40	46	12 / 420

3260P

3/8"

- Extension bar
- DIN 3121




KT NO.	Overall length inch	mm		
3260-03P	3	75	96	6 / 120
3260-04P	4	100	98.6	8 / 160
3260-05P	5	125	145	8 / 144
3260-06P	6	150	168	5 / 100
3260-08P	8	200	216	6 / 72
3260-10P	10	250	230	6 / 54

3796P

3/8"

- Universal joint
- DIN 3121



KT NO.	Overall length inch	mm	D mm		
3796P	2	50	22	83.4	10 / 200

90608

90609

3/8"

- Locking pin
- Chrome vanadium steel
- DIN 3129



KT NO. Desp. Ø d / l Applied to socket sizes

90608	pin	2.5	14	3535M (6~12 mm)	3535S (1/4~1/2 inch)
				3435M (6~12 mm)	3435S (1/4~1/2 inch)
				3055M (4~12 mm)	3055S (3/16~1/2 inch)
				3065M (4~10 mm)	3053 (T10~T15)
				3575M (E5~E14)	
90609	pin	2.5	16	3053, 3055, 3065, 3147, 3862, 3864	
				3535M (13~19 mm)	3535S (9/16~3/4 inch)
				3435M (13~24 mm)	3435S (9/16~7/8 inch)