

Bit Socket



In order to get normal life of bit socket, always use within limited torque to bit.

4021

⊕ 1/2"

- Phillips head
- DIN ISO 8764-1



KT NO.	⊕ No.	Overall length mm		
402102	PH2	60	77	10 / 180
402103	PH3	60	77	10 / 180
402104	PH4	60	77	10 / 180

4025

4035

40D5

⊙ 1/2"

- Hexagon head
- DIN 7422



KT NO.	mm / Inch	Overall length mm		
402503	H3	60	68	10 / 180
402504	H4	60	68	10 / 180
402505	H5	60	70	10 / 180
402506	H6	60	72	10 / 180
402507	H7	60	75	10 / 180
402508	H8	60	75	10 / 180
402509	H9	60	79	10 / 180
402510	H10	60	85	10 / 180
402512	H12	60	117	10 / 180
402514	H14	60	120	10 / 180
402517	H17	66	153	10 / 100
402519	H19	66	225	10 / 120
403504	H4	80	90	6 / 120
403505	H5	80	90	6 / 120
403506	H6	80	90	6 / 120
403507	H7	80	90	6 / 120
403508	H8	80	93	6 / 120
403509	H9	80	97	6 / 120
403510	H10	80	107	6 / 120
403511	H11	80	140	6 / 120
403512	H12	80	145	6 / 120
403514	H14	80	145	6 / 120
403517	H17	80	200	6 / 120
403519	H19	80	245	6 / 96
40D506	H6	140	102	6 / 120
40D508	H8	140	104	6 / 120
40D510	H10	140	133	6 / 120
402506S	3/16	60	66	10 / 180
402507S	7/32	60	68	10 / 180
402508S	1/4	60	69	10 / 180
402509S	9/32	60	70	10 / 180
402510S	5/16	60	74	10 / 180
402512S	3/8	60	83	10 / 180
402514S	7/16	60	100	10 / 180
402516S	1/2	60	110	10 / 180
402518S	9/16	66	157	12 / 120
402520S	5/8	66	162	12 / 120
402524S	3/4	66	225	10 / 120

4022

⊖ 1/2"

- Slotted head
- DIN ISO 5264 / 3120



KT NO.	Tip width mm	Tip thickness mm	Overall length mm		
402208	8	1.2	60	77	10 / 180
402210	10	1.6	60	83	10 / 180
402212	12	2.0	60	110	10 / 180
402214	14	2.5	60	112	10 / 180
402216	16	2.5	60	113	10 / 180

40D0

⬠ 1/2"

- Hexagon with ball point head



KT NO.	mm	Overall length mm		
40D006	H6	140	101	6 / 120
40D008	H8	140	103	6 / 120
40D010	H10	140	132	6 / 120

4026

4036

⬤ 1/2"

4046

4066

- Spline head
- DIN 3120



KT NO.	Size	Overall length mm		
402605	M5	60	70	10 / 180
402606	M6	60	72	10 / 180
402608	M8	60	73	10 / 180
402610	M10	60	85	10 / 180
402612	M12	60	113	10 / 180
402614	M14	60	117	10 / 180
402616	M16	60	145	10 / 120
402618	M18	60	196	10 / 120
403605	M5	80	74	6 / 120
403606	M6	80	85	6 / 120
403608	M8	80	90	6 / 120
403610	M10	80	107	6 / 120
403612	M12	80	142	6 / 120
403614	M14	80	134	6 / 120
404605	M5	100	82	6 / 120
404607	M7	100	84	6 / 120
404608	M8	100	85	6 / 120
404610	M10	100	113	6 / 120
404612	M12	100	138	6 / 120
404614	M14	100	170	6 / 120
406608	M8	140	109	6 / 120
406609	M9	140	138	6 / 120
406610	M10	140	138	6 / 120
406612	M12	140	175	6 / 120
406614	M14	140	213	6 / 120
406616	M16	140	301	6 / 72