

Deep Impact Socket


KT No. & D1



4430M



▪ DIN 3121




KT NO.	\textcircled{O} mm	D1 mm	D2 mm	ℓ mm	L mm			
443008M	8	15.0	25	12	78	130	6 / 120	
443009M	9	16.3	25	12	78	135	6 / 120	
443010M	10	17.6	25	12	80	150	6 / 120	
443011M	11	18.8	25	13	80	160	6 / 120	
443012M	12	20.0	25	14	80	170	6 / 120	
443013M	13	21.2	25	14	80	165	6 / 120	
443014M	14	22.5	25	14	80	180	6 / 120	
443015M	15	23.8	30	16	80	236	6 / 96	
443016M	16	25.0	30	16	80	243	6 / 96	
443017M	17	26.2	30	16	80	255	6 / 96	
443018M	18	27.5	30	17	80	267	6 / 96	
443019M	19	28.8	30	18	80	260	6 / 96	
443020M	20	29.5	30	20	80	252	6 / 96	
443021M	21	30.0	30	20	80	251	6 / 96	
443022M	22	32.4	30	22	80	304	5 / 60	
443023M	23	33.2	30	24	80	310	5 / 60	
443024M	24	34.4	30	24	80	318	5 / 60	
443027M	27	38.0	30	27	80	368	5 / 60	
443030M	30	42.0	30.5	30	80	422	5 / 50	
443032M	32	46.0	30	32	80	460	1 / 24	
443036M	36	47.0	30	36	80	535	1 / 24	

4430S



▪ ANSI / ASME B107.2




KT NO.	\textcircled{O} inch	D1 mm	D2 mm	ℓ mm	L mm			
443020S	5/8	24	25	16	80	233	6 / 96	
443024S	3/4	28.8	30	18	80	250	6 / 96	
443028S	7/8	32	30	22	80	294	5 / 60	
443030S	15/16	34	30	24	80	308	5 / 60	
443032S	1	36	30	24	80	341	5 / 60	
443034S	1-1/16	38	30	27	80	358	5 / 60	
443036S	1-1/8	41	30	27	80	401	5 / 50	
443040S	1-1/4	46	30	32	80	504	1 / 24	
443042S	1-5/16	46	30	34	80	476	1 / 24	
443048S	1-1/2	50	30	34	80	564	1 / 24	

4435M



▪ DIN 3121




KT NO.	\textcircled{O} mm	D1 mm	D2 mm	ℓ mm	L mm			
443508M	8	15.0	25	12	78	116	6 / 120	
443509M	9	16.3	25	12	78	125	6 / 120	
443510M	10	17.6	25	12	80	136	6 / 120	
443511M	11	18.8	25	13	80	144	6 / 120	
443512M	12	20.0	25	14	80	157	6 / 120	
443513M	13	21.2	25	14	80	157	6 / 120	
443514M	14	22.5	25	14	80	172	6 / 120	
443515M	15	23.8	30	16	80	223	6 / 96	
443516M	16	25.0	30	16	80	230	6 / 96	
443517M	17	26.2	30	16	80	240	6 / 96	
443518M	18	27.5	30	17	80	255	6 / 96	
443519M	19	28.8	30	18	80	236	6 / 96	
443520M	20	29.0	30	20	80	244	6 / 96	
443521M	21	30.0	30	20	80	240	6 / 96	
443522M	22	31.8	30	22	80	296	5 / 60	
443523M	23	33.8	30	24	80	300	5 / 60	
443524M	24	33.8	30	24	80	308	5 / 60	
443525M	25	35.8	30	24	80	342	5 / 60	
443526M	26	37.8	30	27	80	344	5 / 60	
443527M	27	38.0	30	27	80	356	5 / 60	
443528M	28	41.0	30	27	80	424	5 / 50	
443529M	29	41.0	30	27	80	404	5 / 50	
443530M	30	42.0	30.5	30	80	416	5 / 50	
443532M	32	46.0	30	32	80	510	1 / 24	
443533M	33	46.0	30	32	80	521	1 / 24	
443534M	34	46.0	30	33	80	539	1 / 24	
443536M	36	47.0	30	36	80	556	1 / 24	
443538M	38	50.0	30	38	80	617	1 / 24	
443541M	41	56.0	30	38	80	635	1 / 24	
443546M	46	64.0	30	40	80	825	1 / 24	

4435S



▪ ANSI / ASME B107.2



KT NO.	\textcircled{O} inch	D1 mm	D2 mm	ℓ mm	L mm			
443510S	5/16	14	25	12	78	123	6 / 120	
443512S	3/8	17	25	12	80	148	6 / 120	
443514S	7/16	18	25	13	80	148	6 / 120	
443516S	1/2	20	25	14	80	159	6 / 120	
443518S	9/16	22	25	14	80	170	6 / 120	
443520S	5/8	24	25	16	80	232	6 / 96	
443522S	11/16	26	30	17	80	235	6 / 96	
443524S	3/4	28.8	30	18	80	251	6 / 96	
443526S	13/16	30	30	20	80	243	6 / 96	
443528S	7/8	32	30	22	80	292	5 / 60	
443530S	15/16	34	30	24	80	308	5 / 60	
443532S	1	36	30	24	80	336	5 / 60	