

Calipers

An industry standard measuring tool

Point Caliper SERIES 573, 536 — ABSOLUTE Digimatic and vernier types

MeasurLink® ENABLED
Data Management Software by Mitutoyo


MeasurLink ENABLED
Data Management Software by Mitutoyo

Products equipped with the measurement data output function can be connected to the measurement data network system MeasurLink (refer to page A-5 for details).

IP67



- Narrow-tip jaws fit into very small grooves and tracks, making many previously difficult outside measurements far easier to obtain.
- Allows step measurement.
- Digimatic models are IP67 Absolute type. No need to reset the origin after switching on. (Refer to page D-8 for a description of Absolute measurement.)
- SPC output models allow integration into statistical process control and measurement systems. Refer to page A-3.



573-621-20
ABSOLUTE™

536-121



Technical Data

- Accuracy: Refer to the list of specifications. (excluding quantizing error for Digimatic models)
- Resolution*1: 0.01 mm or 0.0005 in/0.01 mm
- Graduation*2: 0.05 mm
- Display*1: LCD
- Scale type*1: ABSOLUTE electromagnetic induction linear encoder
- Max. response speed*1: Unlimited
- Battery: SR44 (1 pc), **938882**, for initial operational checks (standard accessory)
- Battery life*1: Approx. 5 years under normal use
- Dust/Water protection level*1: IP67 (IEC 60529)*3
- *1 Digimatic models
- *2 Analog models
- *3 Rustproofing shall be applied after use if caliper was in contact with coolant.

Optional Accessories for Digimatic Models

For details, refer to page D-38.

- Connecting cables for **IT / DP / MUX**
05CZA624: SPC cable with data button (1 m)
05CZA625: SPC cable with data button (2 m)
- USB Input Tool Direct
06AFM380A: SPC cable for **USB-ITN-A** (2 m)
- Connecting cables for **U-WAVE-T**
02AZD790A: SPC cable with data button (160 mm)
02AZE140A: SPC cable for foot switch

Wireless Data Output **U-WAVE fit**

- **U-WAVE-TC: 264-620** (IP67 type)
264-621 (Buzzer type)
 - Connecting unit for **U-WAVE-TC:**
02AZF310 (IP67 type)
- Note: IP67 model is water/dust-proofed suitable for the factory floor.
Buzzer type is not water/dust-proofed.
Refer to page A-15 for details.

SPECIFICATIONS

Metric	Digimatic model	
Order No.	Range (mm)	Accuracy (mm)
573-621-20	0 - 150	±0.02
573-625-20	0 - 150	±0.02
573-622-20*	0 - 150	±0.02
573-626-20*	0 - 150	±0.02

* Without thumb roller

Metric	Analog model	
Order No.	Range (mm)	Accuracy (mm)
536-121	0 - 150	±0.05

Inch / Metric	Digimatic model	
Order No.	Range (in)	Accuracy (in)
573-721-20	0 - 6	±0.001
573-725-20	0 - 6	±0.001

DIMENSIONS

