




# Thin Wall Impact Socket

KT No. &amp; D1


**6835M**

3/4"

- DIN 3121




| KT NO.  | mm | D1 mm | D2 mm | ℓ mm | L mm | g   | kg | kg |
|---------|----|-------|-------|------|------|-----|----|----|
| 683517M | 17 | 28.0  | 44    | 16   | 60   | 320 | 6  | 48 |
| 683519M | 19 | 30.0  | 44    | 16   | 60   | 348 | 6  | 48 |
| 683521M | 21 | 33.0  | 44    | 18   | 60   | 355 | 6  | 48 |
| 683522M | 22 | 34.0  | 44    | 18   | 60   | 362 | 6  | 48 |
| 683523M | 23 | 35.0  | 44    | 23   | 60   | 370 | 6  | 48 |
| 683524M | 24 | 36.5  | 44    | 23   | 60   | 378 | 6  | 48 |
| 683526M | 26 | 39.0  | 44    | 25   | 80   | 400 | 1  | 24 |
| 683527M | 27 | 40.0  | 44    | 26   | 80   | 424 | 1  | 24 |
| 683529M | 29 | 43.0  | 44    | 26   | 80   | 460 | 1  | 24 |
| 683530M | 30 | 44.0  | 44    | 26   | 80   | 478 | 1  | 24 |
| 683532M | 32 | 46.5  | 44    | 26   | 80   | 512 | 1  | 24 |

**6935M**

3/4"

- DIN 3121




| KT NO.  | mm | D1 mm | D2 mm | ℓ mm | L mm | g   | kg | kg |
|---------|----|-------|-------|------|------|-----|----|----|
| 693519M | 19 | 30.0  | 44    | 16   | 90   | 562 | 1  | 24 |
| 693521M | 21 | 33.0  | 44    | 18   | 90   | 597 | 1  | 24 |
| 693522M | 22 | 34.0  | 44    | 18   | 90   | 612 | 1  | 24 |
| 693523M | 23 | 35.0  | 44    | 23   | 90   | 614 | 1  | 24 |
| 693524M | 24 | 36.5  | 44    | 23   | 90   | 619 | 1  | 24 |
| 693526M | 26 | 39.0  | 44    | 25   | 90   | 629 | 1  | 24 |
| 693527M | 27 | 40.0  | 44    | 27   | 90   | 631 | 1  | 24 |
| 693529M | 29 | 43.0  | 44    | 27   | 90   | 672 | 1  | 24 |
| 693530M | 30 | 44.0  | 44    | 27   | 90   | 693 | 1  | 24 |
| 693532M | 32 | 46.5  | 44    | 30   | 90   | 733 | 1  | 24 |

**6935S**

3/4"

- ANSI / ASME B107.2




| KT NO.  | Inch   | D1 mm | D2 mm | ℓ mm | L mm | g   | kg | kg |
|---------|--------|-------|-------|------|------|-----|----|----|
| 693524S | 3/4    | 30.0  | 38    | 16   | 90   | 370 | 1  | 24 |
| 693526S | 13/16  | 33.0  | 38    | 18   | 90   | 380 | 1  | 24 |
| 693528S | 7/8    | 34.0  | 38    | 18   | 90   | 385 | 1  | 24 |
| 693530S | 15/16  | 36.5  | 38    | 23   | 90   | 415 | 1  | 24 |
| 693532S | 1      | 38.0  | 38    | 23   | 90   | 500 | 1  | 24 |
| 693534S | 1-1/16 | 40.0  | 44    | 25   | 90   | 654 | 1  | 24 |
| 693536S | 1-1/8  | 43.0  | 44    | 25   | 90   | 680 | 1  | 24 |
| 693538S | 1-3/16 | 44.0  | 44    | 27   | 90   | 684 | 1  | 24 |
| 693540S | 1-1/4  | 46.5  | 44    | 30   | 90   | 733 | 1  | 24 |

# Impact Star Socket

**6575M**

3/4"

- For torx external screw
- DIN 3121




| KT NO.  | Size | D1 mm | D2 mm | ℓ mm | L mm | g   | kg | kg |
|---------|------|-------|-------|------|------|-----|----|----|
| 657524M | E24  | 32.5  | 44.0  | 17.0 | 50   | 382 | 6  | 48 |
| 657526M | E26  | 35.0  | 44.0  | 19.0 | 60   | 403 | 6  | 48 |
| 657528M | E28  | 36.5  | 44.0  | 25.5 | 60   | 414 | 6  | 48 |
| 657530M | E30  | 37.5  | 44.0  | 27.0 | 65   | 460 | 1  | 24 |
| 657532M | E32  | 39.5  | 44.0  | 29.0 | 65   | 470 | 1  | 24 |

# Deep Impact Star Socket

**6475M**

3/4"

- For torx external screw
- DIN 3121
- For the operation of cylinder head bolts
- E18 application MAN M 2000 / Bus with D 08 engine
- E20 application MAN F 2000 / F 90/ F 8/ Bus with D 25 and D 28 engines
- E24 application MAN D20 engine



| KT NO.  | Size | D1 mm | D2 mm | ℓ mm | L mm | g   | kg | kg |
|---------|------|-------|-------|------|------|-----|----|----|
| 647518M | E18  | 26.5  | 44.0  | 12.5 | 110  | 635 | 1  | 10 |
| 647520M | E20  | 29.0  | 44.0  | 14.0 | 110  | 680 | 1  | 10 |
| 647522M | E22  | 31.0  | 44.0  | 15.0 | 110  | 700 | 1  | 10 |
| 647524M | E24  | 32.5  | 44.0  | 17.0 | 110  | 736 | 1  | 10 |


# Rear Wheel Socket

KT No. &amp; D1


**6514M**

3/4"

- 4 points
- DIN 3121



| KT NO.  | Size | D1 mm | D2 mm | ℓ mm | L mm | g   | kg | kg |
|---------|------|-------|-------|------|------|-----|----|----|
| 651417M | 17   | 39.8  | 34    | 28   | 53   | 350 | 1  | 24 |
| 651419M | 19   | 39.8  | 34    | 28   | 53   | 332 | 1  | 24 |
| 651420M | 20   | 41.8  | 36    | 28   | 53   | 377 | 1  | 24 |
| 651421M | 21   | 41.8  | 36    | 28   | 53   | 370 | 1  | 24 |