



Thin Wall Impact Socket


KT No. & D1



6835M

3/4"

- DIN 3121




KT NO.	mm	D1 mm	D2 mm	ℓ mm	L mm	g	kg	kg
683517M	17	28.0	44	16	60	320	6	48
683519M	19	30.0	44	16	60	348	6	48
683521M	21	33.0	44	18	60	355	6	48
683522M	22	34.0	44	18	60	362	6	48
683523M	23	35.0	44	23	60	370	6	48
683524M	24	36.5	44	23	60	378	6	48
683526M	26	39.0	44	25	80	400	1	24
683527M	27	40.0	44	26	80	424	1	24
683529M	29	43.0	44	26	80	460	1	24
683530M	30	44.0	44	26	80	478	1	24
683532M	32	46.5	44	26	80	512	1	24

6935M

3/4"

- DIN 3121




KT NO.	mm	D1 mm	D2 mm	ℓ mm	L mm	g	kg	kg
693519M	19	30.0	44	16	90	562	1	24
693521M	21	33.0	44	18	90	597	1	24
693522M	22	34.0	44	18	90	612	1	24
693523M	23	35.0	44	23	90	614	1	24
693524M	24	36.5	44	23	90	619	1	24
693526M	26	39.0	44	25	90	629	1	24
693527M	27	40.0	44	27	90	631	1	24
693529M	29	43.0	44	27	90	672	1	24
693530M	30	44.0	44	27	90	693	1	24
693532M	32	46.5	44	30	90	733	1	24

6935S

3/4"

- ANSI / ASME B107.2




KT NO.	Inch	D1 mm	D2 mm	ℓ mm	L mm	g	kg	kg
693524S	3/4	30.0	38	16	90	370	1	24
693526S	13/16	33.0	38	18	90	380	1	24
693528S	7/8	34.0	38	18	90	385	1	24
693530S	15/16	36.5	38	23	90	415	1	24
693532S	1	38.0	38	23	90	500	1	24
693534S	1-1/16	40.0	44	25	90	654	1	24
693536S	1-1/8	43.0	44	25	90	680	1	24
693538S	1-3/16	44.0	44	27	90	684	1	24
693540S	1-1/4	46.5	44	30	90	733	1	24

Impact Star Socket

6575M

3/4"

- For torx external screw
- DIN 3121




KT NO.	Size	D1 mm	D2 mm	ℓ mm	L mm	g	kg	kg
657524M	E24	32.5	44.0	17.0	50	382	6	48
657526M	E26	35.0	44.0	19.0	60	403	6	48
657528M	E28	36.5	44.0	25.5	60	414	6	48
657530M	E30	37.5	44.0	27.0	65	460	1	24
657532M	E32	39.5	44.0	29.0	65	470	1	24

Deep Impact Star Socket

6475M

3/4"

- For torx external screw
- DIN 3121
- For the operation of cylinder head bolts
- E18 application MAN M 2000 / Bus with D 08 engine
- E20 application MAN F 2000 / F 90/ F 8/ Bus with D 25 and D 28 engines
- E24 application MAN D20 engine



KT NO.	Size	D1 mm	D2 mm	ℓ mm	L mm	g	kg	kg
647518M	E18	26.5	44.0	12.5	110	635	1	10
647520M	E20	29.0	44.0	14.0	110	680	1	10
647522M	E22	31.0	44.0	15.0	110	700	1	10
647524M	E24	32.5	44.0	17.0	110	736	1	10

Rear Wheel Socket


KT No. & D1



6514M

3/4"

- 4 points
- DIN 3121



KT NO.	Size	D1 mm	D2 mm	ℓ mm	L mm	g	kg	kg
651417M	17	39.8	34	28	53	350	1	24
651419M	19	39.8	34	28	53	332	1	24
651420M	20	41.8	36	28	53	377	1	24
651421M	21	41.8	36	28	53	370	1	24