



SIMATIC ET 200SP, Analog input module, AI Energy Meter 400 V AC ST, suitable for BU type D0, channel diagnostics

General information	
Product type designation	AI energy meter 400VAC ST
Firmware version	V3.0
usable BaseUnits	BU type D0
Product function	
<ul style="list-style-type: none"> • Voltage measurement <ul style="list-style-type: none"> — with voltage transformer • Current measurement <ul style="list-style-type: none"> — without current transformer — with current transformer • Energy measurement • Frequency measurement • Power measurement • Active power measurement • Reactive power measurement • I&M data • Isochronous mode 	Yes No Yes No Yes Yes Yes Yes Yes Yes Yes; I&M0 to I&M3 No
Engineering with	
<ul style="list-style-type: none"> • STEP 7 TIA Portal configurable/integrated from version • STEP 7 configurable/integrated from version • PROFIBUS from GSD version/GSD revision • PROFINET from GSD version/GSD revision 	V13 SP1 V5.5 SP4 and higher GSD Revision 5 V2.3
Operating mode	
<ul style="list-style-type: none"> • cyclic measurement • acyclic measurement • Acyclic measured value access • Fixed measured value sets • Freely definable measured value sets 	Yes Yes Yes Yes No
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	No
Installation type/mounting	
Mounting position	any
Supply voltage	
Design of the power supply	Supply via voltage measurement channel L1
Rated value (AC)	100 - 240 V AC
permissible range, lower limit (AC)	90 V
permissible range, upper limit (AC)	264 V
Line frequency	
<ul style="list-style-type: none"> • permissible range, lower limit 	47 Hz

<ul style="list-style-type: none"> • permissible range, upper limit 	63 Hz
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
<ul style="list-style-type: none"> • Address space per module, max. 	44 byte; 32 byte input / 12 byte output
Hardware configuration	
Automatic encoding	
<ul style="list-style-type: none"> • Mechanical coding element • Type of mechanical coding element 	Yes type C
Time of day	
Operating hours counter	
<ul style="list-style-type: none"> • present 	No
Analog inputs	
Cycle time (all channels), typ.	50 ms; Time for consistent update of all measured and calculated values (cyclic und acyclic data)
Interrupts/diagnostics/status information	
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm • Limit value alarm • Hardware interrupt 	Yes No No
Diagnostics indication LED	
<ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) • Channel status display • for channel diagnostics • for module diagnostics 	Yes Yes; green LED Yes; red Fn LED Yes; green/red DIAG LED
Integrated Functions	
Measuring functions	
<ul style="list-style-type: none"> • Measuring procedure for voltage measurement • Measuring procedure for current measurement • Type of measured value acquisition • Curve shape of voltage • Buffering of measured variables • Parameter length • Bandwidth of measured value acquisition 	TRMS TRMS seamless Sinusoidal or distorted No 38 byte 2 kHz; Harmonics: 39 / 50 Hz, 32 / 60 Hz
Measuring range	
<ul style="list-style-type: none"> — Frequency measurement, min. — Frequency measurement, max. 	45 Hz 65 Hz
Measuring inputs for voltage	
<ul style="list-style-type: none"> — Measurable line voltage between phase and neutral conductor — Measurable line voltage between the line conductors — Measurable line voltage between phase and neutral conductor, min. — Measurable line voltage between phase and neutral conductor, max. — Measurable line voltage between the line conductors, min. — Measurable line voltage between the line conductors, max. — Internal resistance line conductor and neutral conductor — Power consumption per phase — Impulse voltage resistance 1,2/50μs — Measurement category for voltage measurement in accordance with IEC 61010-2-030 	230 V 400 V 90 V 264 V 155 V 460 V 3.4 M Ω 20 mW 1 kV CAT II; CAT III in case of guaranteed protection level of 1.5 kV
Measuring inputs for current	
<ul style="list-style-type: none"> — measurable relative current (AC), min. — measurable relative current (AC), max. — Continuous current with AC, maximum permissible — Apparent power consumption per phase for 	5 %; Relative to the secondary rated current; 1 A, 5 A 100 %; Relative to the secondary rated current; 1 A, 5 A 5 A 0.6 VA

measuring range 5 A	
— Rated value short-time withstand current restricted to 1 s	100 A
— Input resistance measuring range 0 to 5 A	25 mΩ; At the terminal
— Surge strength	10 A; for 1 minute
— Zero point suppression	Parameterizable: 20 ... 250 mA, default 50 mA
Accuracy class according to IEC 61557-12	
— Measured variable voltage	0.5
— Measured variable current	0.5
— Measured variable apparent power	1
— Measured variable active power	1
— Measured variable reactive power	1
— Measured variable power factor	0.5
— Measured variable active energy	1
— Measured variable reactive energy	2
— Measured variable phase angle	±1 °; not covered by IEC 61557-12
— Measured variable frequency	0.05
Potential separation	
Potential separation channels	
• between the channels and backplane bus	Yes; 3 700V AC (type test) CAT III
Isolation	
Isolation tested with	2 300V AC for 1 min. (type test)
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	50 °C
Dimensions	
Width	20 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	45 g
Other	
Data for selecting a current transformer	
• Burden power current transformer x/1A, min.	As a function of cable length and cross section, see device manual
• Burden power current transformer x/5A, min.	As a function of cable length and cross section, see device manual
last modified:	12/28/2021 