


## Socket Set

**8330M**

1"

- DIN 3124, ISO 2725-1




| KT NO.  | mm | D1 mm | D2 mm | ℓ mm | L mm |      |        |
|---------|----|-------|-------|------|------|------|--------|
| 833036M | 36 | 52    | 48    | 26   | 65   | 449  | 1 / 24 |
| 833038M | 38 | 54    | 48    | 26   | 65   | 478  | 1 / 24 |
| 833041M | 41 | 58    | 50    | 29   | 70   | 557  | 1 / 24 |
| 833046M | 46 | 65    | 54    | 32   | 75   | 849  | 1 / 24 |
| 833050M | 50 | 70    | 54    | 34   | 75   | 996  | 1 / 20 |
| 833054M | 54 | 74    | 57    | 38   | 80   | 1145 | 1 / 20 |
| 833055M | 55 | 76    | 57    | 42   | 83   | 1206 | 1 / 12 |
| 833058M | 58 | 79    | 57    | 42   | 83   | 1263 | 1 / 12 |
| 833060M | 60 | 82    | 58    | 46   | 87   | 1470 | 1 / 12 |
| 833063M | 63 | 86    | 58    | 46   | 87   | 1555 | 1 / 12 |
| 833065M | 65 | 88    | 65    | 49   | 90   | 1670 | 1 / 12 |
| 833067M | 67 | 91    | 70    | 49   | 91   | 1670 | 1 / 12 |
| 833070M | 70 | 94    | 70    | 50   | 93   | 2100 | 1 / 8  |
| 833071M | 71 | 95    | 70    | 50   | 93   | 2068 | 1 / 8  |
| 833075M | 75 | 100   | 70    | 50   | 95   | 2310 | 1 / 8  |
| 833077M | 77 | 103   | 80    | 52   | 100  | 2557 | 1 / 8  |
| 833080M | 80 | 107   | 80    | 52   | 100  | 2580 | 1 / 8  |

**8330S**

1"

- ANSI / ASME B107.1




| KT NO.  | inch    | D1 mm | D2 mm | ℓ mm | L mm |      |        |
|---------|---------|-------|-------|------|------|------|--------|
| 833046S | 1-7/16  | 52    | 48    | 26   | 65   | 463  | 1 / 24 |
| 833048S | 1-1/2   | 54    | 48    | 26   | 65   | 489  | 1 / 24 |
| 833054S | 1-11/16 | 60    | 54    | 29   | 70   | 680  | 1 / 24 |
| 833060S | 1-7/8   | 67    | 54    | 34   | 75   | 976  | 1 / 10 |
| 833064S | 2       | 71    | 54    | 34   | 75   | 988  | 1 / 10 |
| 833072S | 2-1/4   | 78    | 57    | 42   | 83   | 1212 | 1 / 12 |
| 833076S | 2-3/8   | 82    | 58    | 46   | 87   | 1437 | 1 / 12 |
| 833084S | 2-5/8   | 90    | 65    | 49   | 90   | 1693 | 1 / 12 |
| 833094S | 2-15/16 | 100   | 70    | 52   | 95   | 2242 | 1 / 8  |
| 8330AQS | 3-1/8   | 107   | 80    | 52   | 100  | 2578 | 1 / 8  |

## Ratchet

**8779**

1"

- Reversible ratchet
- 15° gear action degree (24 teeth)
- DIN 3122



8779DK

| KT NO.   | Overall length<br>inch | mm  |      |   |
|----------|------------------------|-----|------|---|
| 8779-32F | 32                     | 800 | 4400 | 5 |
| 8779DK   | renewal kits           |     | -    | - |

## Accessory

- Chrome vanadium handle, chrome molybdenum driver
- Chrome plated handle & black phosphate sunk driver

**8251**

1"

- Extension bar
- DIN3123



| KT NO.  | Overall length<br>inch | mm  |      |        |
|---------|------------------------|-----|------|--------|
| 8251-08 | 8                      | 200 | 1350 | 1 / 16 |
| 8251-16 | 16                     | 400 | 2480 | 1 / 10 |

**8572**

1"

- Sliding T-handle
- DIN 3122



8572DK

| KT NO.  | Overall length<br>inch | mm  |      |   |
|---------|------------------------|-----|------|---|
| 8572-25 | 25                     | 630 | 4200 | 6 |
| 8572DK  | renewal kits           |     | -    | - |

**8581**

1"

- L-handle
- DIN 3122



| KT NO.  | Overall length<br>inch | mm  |      |   |
|---------|------------------------|-----|------|---|
| 8581-26 | 26                     | 650 | 5120 | 4 |

**8816**

1"

- Adapter
- Convert to 3/4" drive
- Max. torque : 1412 Nm
- DIN 3123, ISO 3316

3/4" drive(M)



1" drive(F)

| KT NO. | Spec.       |     |        |  |
|--------|-------------|-----|--------|--|
| 8816   | 1"F x 3/4"M | 330 | 6 / 48 |  |