


Socket Set

8330M

1"

• DIN 3124, ISO 2725-1




KT NO.	mm	D1 mm	D2 mm	ℓ mm	L mm		
833036M	36	52	48	26	65	449	1 / 24
833038M	38	54	48	26	65	478	1 / 24
833041M	41	58	50	29	70	557	1 / 24
833046M	46	65	54	32	75	849	1 / 24
833050M	50	70	54	34	75	996	1 / 20
833054M	54	74	57	38	80	1145	1 / 20
833055M	55	76	57	42	83	1206	1 / 12
833058M	58	79	57	42	83	1263	1 / 12
833060M	60	82	58	46	87	1470	1 / 12
833063M	63	86	58	46	87	1555	1 / 12
833065M	65	88	65	49	90	1670	1 / 12
833067M	67	91	70	49	91	1670	1 / 12
833070M	70	94	70	50	93	2100	1 / 8
833071M	71	95	70	50	93	2068	1 / 8
833075M	75	100	70	50	95	2310	1 / 8
833077M	77	103	80	52	100	2557	1 / 8
833080M	80	107	80	52	100	2580	1 / 8

8330S

1"

• ANSI / ASME B107.1




KT NO.	inch	D1 mm	D2 mm	ℓ mm	L mm		
833046S	1-7/16	52	48	26	65	463	1 / 24
833048S	1-1/2	54	48	26	65	489	1 / 24
833054S	1-11/16	60	54	29	70	680	1 / 24
833060S	1-7/8	67	54	34	75	976	1 / 10
833064S	2	71	54	34	75	988	1 / 10
833072S	2-1/4	78	57	42	83	1212	1 / 12
833076S	2-3/8	82	58	46	87	1437	1 / 12
833084S	2-5/8	90	65	49	90	1693	1 / 12
833094S	2-15/16	100	70	52	95	2242	1 / 8
8330A0S	3-1/8	107	80	52	100	2578	1 / 8

Ratchet

8779

1"

- Reversible ratchet
- 15° gear action degree (24 teeth)
- DIN 3122



8779DK

KT NO.	Overall length inch	mm		
8779-32F	32	800	4400	5
8779DK	renewal kits		-	-

Accessory

- Chrome vanadium handle, chrome molybdenum driver
- Chrome plated handle & black phosphate sunk driver

8251

1"

- Extension bar
- DIN3123



KT NO.	Overall length inch	mm		
8251-08	8	200	1350	1 / 16
8251-16	16	400	2480	1 / 10

8572

1"

- Sliding T-handle
- DIN 3122



8572DK

KT NO.	Overall length inch	mm		
8572-25	25	630	4200	6
8572DK	renewal kits		-	-

8581

1"

- L-handle
- DIN 3122



KT NO.	Overall length inch	mm		
8581-26	26	650	5120	4

8816

1"

- Adapter
- Convert to 3/4" drive
- Max. torque : 1412 Nm
- DIN 3123, ISO 3316

3/4" drive(M)



1" drive(F)

KT NO.	Spec.			
8816	1"F x 3/4"M	330	6 / 48	