


8435S



S Long imperial 6 points impact socket

ANSI / ASME B107.1

- Inch
- Chrome molybdenum, phosphate finish



	Dimension (Inch)	D1 (mm)	D2 (mm)	L (mm)	l (mm)	Weight (g)
843530S	15/16"	41	54	90	25	850
843532S	1"	42	54	90	25	860
843534S	1-1/16"	44	54	90	25	879
843536S	1-1/8"	47	54	90	25	900
843538S	1-3/16"	48	54	90	28	916
843540S	1-1/4"	51	54	90	28	979
843542S	1-5/16"	52	54	92	28	1016
843544S	1-3/8"	54	54	92	28	1016
843546S	1-7/16"	56	54	92	32	1033
843548S	1-1/2"	58	54	92	32	1025
843550S	1-9/16"	60	54	92	32	1075
843552S	1-5/8"	61	54	92	32	1083
843554S	1-11/16"	64	54	92	32	1100

843556S	1-3/4"	67	54	92	32	1120
843558S	1-13/16"	68	54	95	35	1137
843560S	1-7/8"	70	54	95	35	1400
843562S	1-15/16"	72	54	95	35	1480
843564S	2"	74	54	95	35	1577
843566S	2-1/16"	75	54	100	40	1637
843568S	2-1/8"	78	54	100	40	1750
843570S	2-3/16"	79	54	100	40	1862
843572S	2-1/4"	82	54	100	42	1900