



## MATERIAL FACT SHEET

### 140146 AJ65SBT-64AD

#### General Data

Product Hierarchy	IAD50501
	Modular PLC
	A2C-PLC
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	B (Limited Availability from Stock)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000140146](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000140146)

#### FA-MOD PLC: Analogue I/O Module

Series	CC-LINK
Type	REMOTE ANALOG INPUT
Power Supply (V)	24
Current Type	DC
Occupied Stations	1
Integrated Analogue Inputs	4
Input Voltage Range (V)	-10-10; 0-5; 1-5
Input Current Range (mA)	0-20; 4-20
Wiring	SCREW
Int. Current Consumption (A)	0,09

#### Product Dimensions & Weight

Width (mm)	118
Height (mm)	50
Depth (mm)	40
Weight (kg)	0,2

#### Logistic Dimensions & Gross Weight

Length (cm)	17,0
Width (cm)	8,0
Height (cm)	6,5
Gross Weight (kg)	0,248
Volume (cdm)	0,884

#### Stock Data

Planned Delivery Time (Days)	75
------------------------------	----

#### Life Cycle

Sales Start	29.11.2001
Predecessor	No Predecessor

#### Additional Product Information

Binding Tariff Information	DEBTI-10685/21-1
BTI validity date	31.10.2024
Battery included	NO
Forecast Breakdown	A2C-PLC

#### Export Data

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	<a href="#">7439-92-1</a>

REACH Substance CAS Number (2)	<a href="#">80-05-7</a>
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

### Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
UKCA	COMPLIANT

### Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=AJ65SBT-64AD&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=AJ65SBT-64AD&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=AJ65SBT-64AD&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=AJ65SBT-64AD&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=AJ65SBT-64AD&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=AJ65SBT-64AD&amp;doc-lang=en</a>
Network configuration file URL	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blte8cf990c7c524b4e&amp;q=AJ65SBT-64AD&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blte8cf990c7c524b4e&amp;q=AJ65SBT-64AD&amp;doc-lang=en</a>

### Product Packaging

Cardboard (g)	75
Other paper (g)	1
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	5
Wood (g)	0
Glass (g)	0
Others (g)	0



## MATERIAL FACT SHEET

### 251330 AJ65SBT2B-64AD

#### General Data

Product Hierarchy	IAD50501
	Modular PLC
	A2C-PLC
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000251330](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000251330)

#### FA-MOD PLC: Analogue I/O Module

Series	CC-LINK
Type	REMOTE ANALOG INPUT
Power Supply (V)	24
Current Type	DC
Occupied Stations	1
Integrated Analogue Inputs	4
Input Voltage Range (V)	-10-10; 0-5; 1-5
Input Current Range (mA)	0-20; 4-20
Wiring	SCREW
Int. Current Consumption (A)	0,12

#### Product Dimensions & Weight

Width (mm)	122
Height (mm)	50
Depth (mm)	54
Weight (kg)	0,25

#### Logistic Dimensions & Gross Weight

Length (cm)	13,7
Width (cm)	9,5
Height (cm)	10,5
Gross Weight (kg)	0,359
Volume (cdm)	1,367

#### Stock Data

Planned Delivery Time (Days)	136
------------------------------	-----

#### Life Cycle

Sales Start	05.07.2012
Predecessor	75444 / AJ65BT-64AD

#### Additional Product Information

Binding Tariff Information	DEBTI-10685/21-1
BTI validity date	31.10.2024
Battery included	NO
Forecast Breakdown	A2C-PLC

#### Export Data

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	<a href="#">7439-92-1</a>

REACH Substance CAS Number (2)	<a href="#">80-05-7</a>
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
RoHS Compliance	COMPLIANT
WEEE	B2B

### Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	COMPLIANT
UKCA	COMPLIANT

### Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=AJ65SBT2B-64AD&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=AJ65SBT2B-64AD&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=AJ65SBT2B-64AD&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=AJ65SBT2B-64AD&amp;doc-lang=en</a>
Network configuration file URL	X

### Product Packaging

Cardboard (g)	80
Other paper (g)	1
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	5
Wood (g)	0
Glass (g)	0
Others (g)	0