


BUTT CONNECTORS (BV)




Insulation: Vinyl
Raw material: Copper or Brass
Plating: Tin



Item No.	Wire Range mm ² (A.W.G.)	Dimension(mm)			I _{max} .	Color
		I	d	L		
BV 125	0.5-1.5(22-16)	15	1.8	25.5	19A	Red
BV 2	1.5-2.5(16-14)	15	2.4	25.5	27A	Blue
BV 5.5	4-6(12-10)	15	3.6	27.5	48A	Yellow
BV 8	6-10(8)	21	4.7	32.0	62A	Red
BV 14	10-16(6)	26.0	5.8	42.0	88A	Blue
BV 22	16-25(4)	29.0	7.7	50.0	115A	Yellow
BV 38	25-35(2)	32.0	9.4	55.0	160A	Red

MALE PRE-INSULATING JOINT (MDD)



Insulation: Vinyl
Raw material: Brass
Plating: Tin



Item No.	Wire Range mm ² (A.W.G.)	Connecting spec. (mm)	Thickness (mm)	Dimension(mm)					Color
				B	dφ	Dφ	L	H	
MDD 125-110(5)	0.5-1.5 (22-16)	0.5 x 2.8	0.5	2.8	1.7	4.3	17.7	10.0	Red
MDD 125-110(8)		0.8 x 2.8	0.8	2.8	1.7	4.3	17.7	10.0	
MDD 125-187(5)	1.5-2.5 (16-14)	0.5 x 4.75	0.5	4.75	1.7	4.3	20.0	10.0	Blue
MDD 125-187(8)		0.8 x 4.75	0.8	4.75	1.7	4.3	20.0	10.0	
MDD 125-250	4-6 (12-10)	0.8 x 6.35	0.4	6.35	1.7	4.3	21.0	10.0	Yellow
MDD 2-110(5)		0.5 x 2.8	0.5	2.8	2.3	4.9	17.7	10.0	
MDD 2-110(8)	0.5 x 4.75 (16-14)	0.8 x 2.8	0.8	2.8	2.3	4.9	17.7	10.0	Blue
MDD 2-187(5)		0.5 x 4.75	0.5	4.75	2.3	4.9	20.0	10.0	
MDD 2-187(8)	MDD 2-250	0.8 x 4.75	0.8	4.75	2.3	4.9	20.0	10.0	
MDD 2-250		0.8 x 6.35	0.4	6.35	2.3	4.9	21.0	10.0	
MDD 5.5-187(5)	MDD 5.5-250	0.5 x 4.75	0.5	4.75	3.4	6.7	23.0	13.0	Yellow
MDD 5.5-250		0.8 x 6.35	0.4	6.35	3.4	6.7	25.0	13.0	