


# Complete Fixed Device

## ComPacT NSX400/630F (36 kA 380/415 V)


### ComPacT NSX400/630F

Electronic trip unit MicroLogic 2.3 (LS<sub>0</sub>I protection)




ComPacT NSX400F (36 kA at 380/415 V)	250 A	<b>3P 3d</b>	<b>4P 3d, 4d, 3d + N/2</b>
	400 A	<b>C40F32D250</b>	<b>C40F42D250</b>
ComPacT NSX630F (36 kA at 380/415 V)	630 A	<b>C40F32D400</b>	<b>C40F42D400</b>
		<b>C63F32D630</b>	<b>C63F42D630</b>

Electronic trip unit MicroLogic Vigi 4.3 (LS<sub>0</sub>IR protection)




ComPacT NSX400F (36 kA at 380/415 V)	400 A	<b>3P 3d</b>	<b>4P 4d 3d + N/2</b>
		<b>C40F34V400</b>	<b>C40F44V400</b>
ComPacT NSX630F (36 kA at 380/415 V)	570 A	<b>C63F34V570</b>	<b>C63F44V570</b>

Electronic trip unit MicroLogic 1.3 M (I motor protection)



ComPacT NSX400F 1.3 M (36 kA at 380/415V)	320 A	<b>3P 3d</b>	
		<b>C40F31M320</b>	
ComPacT NSX630F 1.3 M (36 kA at 380/415V)	500 A	<b>C63F31M500</b>	

Electronic trip unit MicroLogic 2.3 M (LS<sub>0</sub>I motor protection)



ComPacT NSX400F 2.3 M (36 kA at 380/415V)	320 A	<b>3P 3d</b>	
		<b>C40F32M320</b>	
ComPacT NSX630F 2.3 M (36 kA at 380/415V)	500 A	<b>C63F32M500</b>	

With electronic trip unit MicroLogic 5.3 E (LSI protection, energy meter)

Only available as separate component or through online configurator (product selector)

With electronic trip unit MicroLogic 6.3 E (LSIG protection, energy meter)

Only available as separate component or through online configurator (product selector)

With electronic trip unit MicroLogic 6.3 E-M (LSIG motor protection, energy meter)

Only available as separate component or through online configurator (product selector)

With electronic trip unit MicroLogic 7.3 E (LSIG protection, energy meter)

Only available as separate component or through online configurator (product selector)

F