

CIRCULAR SAWS



8-1/4" (210 mm)
Circular Saw with
Rear Pivot



7-1/4" (184 mm)
Circular Saw with
Rear Pivot



7-1/4" (184 mm)
Worm Drive
Circular Saw



7-1/4" (184 mm)
Lightweight
Circular Saw



7-1/4" (184 mm)
Lightweight Circular Saw
w/ Electric Brake



Dust collection adapter

SPECIFICATIONS	DW384	DW364	DWS535 / DWS535T	DWE575	DWE575SB	DWE575DC
Amps	15 Amps	15 Amps	15 Amps	15 Amps	15 Amps	—
Max Watts Out	2,075 W	2,075 W	2,100 W	1,950 W	1,950 W	—
No Load Speed	5,800 rpm	5,800 rpm	4,800 rpm	5,200 rpm	5,200 rpm	—
Bevel Capacity	50°	50°	53°	57°	57°	—
Bevel Stops	N/A	N/A	45° / 22.5°	45° / 22.5°	45° / 22.5°	—
Rear Pivot	Yes	Yes	No	No	No	—
Electric Brake	Yes	Yes	No	No	Yes	—
Blade Diameter	8-1/4"	7-1/4"	7-1/4"	7-1/4"	7-1/4"	—
Depth Of Cut At 90°	2-15/16"	2-7/16"	2-7/16"	2.55"	2.55"	—
Depth Of Cut At 45°	2-1/4"	1-7/8"	1-7/8"	1-7/8"	1-7/8"	1-7/8"
Includes	Carbide tipped blade and blade wrench	Carbide tipped blade and blade wrench	Carbide tipped 7-1/4" blade, blade wrench / carbide tipped 7-1/4" blade, blade wrench, pre-installed w/ twistlock plug	Carbide tipped 7-1/4" blade and blade wrench	Carbide tipped 7-1/4" blade and blade wrench	Replacement lower guard lever and fastening screws (3)