



Product data sheet

Power tools for trade & industry

Cordless Combi

GSB 18V-150 C



When strength counts – the clever impact drill driver for unrivalled power and control

The most important data

Torque (soft/hard/max.)	84/100/150 Nm
No-load speed (1st gear / 2nd gear)	0 – 550 / 0 – 2,200 rpm
Max. screw diameter	13 mm

Part Number 0 601 9J5 101[> More product information](#)

Technical data

Technical data

Torque (soft/hard/max.)	84/100/150 Nm
No-load speed (1st gear / 2nd gear)	0 – 550 / 0 – 2,200 rpm
Battery type	Lithium-ion
Max. impact rate	30,000 bpm
Chuck capacity, min./max.	1.5 / 13 mm
Battery voltage	18 V
Weight excl. battery	2.2 kg
Torque settings	25+2

'Total vibration values (Drilling in metal)'

Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²

'Total vibration values (Impact drilling in masonry)'

Vibration emission value ah	9.5 m/s ²
Uncertainty K	1.5 m/s ²

Drilling diameter

Max. drilling diameter in wood	150 mm
Max. drilling diameter in steel	16 mm
Max. drilling diameter in masonry	20 mm

Screw diameter

Max. screw diameter	13 mm
---------------------	-------

Noise/vibration information

Drilling in metal

Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²

Impact drilling in masonry

Vibration emission value ah	9.5 m/s ²
Uncertainty K	1.5 m/s ²



BOSCH

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Extremely fast work progress through a powerful brushless motor with a maximum torque of 150 Nm and ProCORE18V batteries
- Precise Electronic Angle Detection and switchable KickBack Control enable unrivalled control at each work stage
- Reliable and robust thanks to metal drill chuck and metal gearbox

