



Product data sheet

HDSF316IP441

Characteristics

Fixed industrial socket, HDSF, 2P + E, 110..130 V, 16 A, IP44



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	16 A
Poles description	2P + E
[Ue] rated operational voltage	110...130 V
Network type	AC
Network frequency	50/60 Hz
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP44

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Product data sheet

HDSF532IP44

Characteristics

Fixed industrial socket, HDSF, 3P + N + E, 240..415 V, 32 A, IP44



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Red

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	32 A
Poles description	3P + N + E
[Ue] rated operational voltage	240...415 V
Network type	AC
Network frequency	50/60 Hz
Height	143 mm
Width	104 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP44



Product data sheet

HDSF516IP44

Characteristics

Fixed industrial socket, HDSF, 3P + N + E, 220..380 V, 16 A, IP44



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Red

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	16 A
Poles description	3P + N + E
[Ue] rated operational voltage	220...380 V
Network type	AC
Network frequency	50/60 Hz
Height	129 mm
Width	96 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP44



Product data sheet

HDSF432IP44

Characteristics

Fixed industrial socket, HDSF, 3P + E, 380..415 V, 32 A, IP44



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Red

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	32 A
Poles description	3P + E
[Ue] rated operational voltage	380...415 V
Network type	AC
Network frequency	50/60 Hz
Height	141 mm
Width	97 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP44



Product data sheet

HDSF416IP44

Characteristics

Fixed industrial socket, HDSF, 3P + E, 380..415 V, 16 A, IP44



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Red

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	16 A
Poles description	3P + E
[Ue] rated operational voltage	380...415 V
Network type	AC
Network frequency	50/60 Hz
Height	128 mm
Width	90 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP44

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Product data sheet

HDSF5125IP67

Characteristics

Fixed industrial socket, HDSF, 3P + N + E, 240..415 V, 125 A, IP67



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Red

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	125 A
Poles description	3P + N + E
[Ue] rated operational voltage	240...415 V
Network type	AC
Network frequency	50/60 Hz
Height	320 mm
Width	140 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP67



Product data sheet

HDSF463IP67

Characteristics

Fixed industrial socket, HDSF, 3P + E, 380..415 V, 63 A, IP67



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Red

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	63 A
Poles description	3P + E
[Ue] rated operational voltage	380...415 V
Network type	AC
Network frequency	50/60 Hz
Height	270 mm
Width	122 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP67



Product data sheet

HDSF4125IP67

Characteristics

Fixed industrial socket, HDSF, 3P + E, 380..415 V, 125 A, IP67



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Red

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	125 A
Poles description	3P + E
[Ue] rated operational voltage	380...415 V
Network type	AC
Network frequency	50/60 Hz
Height	320 mm
Width	140 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP67

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Product data sheet

HDSF363IP67

Characteristics

Fixed industrial socket, HDSF, 2P + E, 220..250 V, 63 A, IP67



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Blue

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	63 A
Poles description	2P + E
[Ue] rated operational voltage	220...250 V
Network type	AC
Network frequency	50/60 Hz
Height	270 mm
Width	122 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP67



Product data sheet

HDSF332IP44

Characteristics

Fixed industrial socket, HDSF, 2P + E, 220..250 V, 32 A, IP44



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Blue

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	32 A
Poles description	2P + E
[Ue] rated operational voltage	220...250 V
Network type	AC
Network frequency	50/60 Hz
Height	141 mm
Width	97 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP44



Product data sheet

HDSF332IP44

Characteristics

Fixed industrial socket, HDSF, 2P + E, 220..250 V, 32 A, IP44



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Blue

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	32 A
Poles description	2P + E
[Ue] rated operational voltage	220...250 V
Network type	AC
Network frequency	50/60 Hz
Height	141 mm
Width	97 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP44



Product data sheet

HDSF316IP44

Characteristics

Fixed industrial socket, HDSF, 2P + E, 220..250 V, 16 A, IP44



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Blue

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	16 A
Poles description	2P + E
[Ue] rated operational voltage	220...250 V
Network type	AC
Network frequency	50/60 Hz
Height	128 mm
Width	86 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP44

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Product data sheet

HDSF3125IP67

Characteristics

Fixed industrial socket, HDSF, 2P + E, 220..250 V, 125 A, IP67



Main

Range of product	HD
Device short name	HDSF
Device application	Power supply
Product or component type	Industrial socket-outlet
Body type	Fixed
Plug, socket category	Low voltage
Outlet standard	Industrial
Voltage colour	Blue

Complementary

Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	125 A
Poles description	2P + E
[Ue] rated operational voltage	220...250 V
Network type	AC
Network frequency	50/60 Hz
Height	320 mm
Width	140 mm
Market segment	Industry

Environment

Standards	IEC 60309
IP degree of protection	IP67