

Product variant	Safe series connections	Connection type	Length of cable	Challenge	Product segment	Product subsegment	Certificate
IQB2S12-04B4DQ9	with Flexi Loop (with diagnostics)	Cable with M12 male connector, 4-pin	0.3 m	No wear, Heavy contamination, Simple diagnostics	Safety switches, Inductive proximity sensors	Non-contact safety switches, Inductive proximity sensors	EU declaration of conformity, UK declaration of conformity, ACMA declaration of conformity, Moroccan declaration of conformity, China-RoHS, UK-Type-Examination approval, cULus certificate, EC-Type-Examination approval, Third party certificate
IQB2S12-04B4DW2	None, only individual wiring (with diagnostics)	Cable, 4-wire	2 m	No wear, Heavy contamination, Simple diagnostics	Safety switches, Inductive proximity sensors	Non-contact safety switches, Inductive proximity sensors	EU declaration of conformity, UK declaration of conformity, ACMA declaration of conformity, Moroccan declaration of conformity, China-RoHS, UK-Type-Examination approval, cULus certificate, EC-Type-Examination approval, Third party certificate
IQB2S12-04B4DT0	None, only individual wiring (with diagnostics)	male connector M8, 4-pin		No wear, Heavy contamination, Simple diagnostics	Safety switches, Inductive proximity sensors	Non-contact safety switches, Inductive proximity sensors	EU declaration of conformity, UK declaration of conformity, ACMA declaration of conformity, Moroccan declaration of conformity, China-RoHS, UK-Type-Examination approval, cULus certificate, EC-Type-Examination approval, Third party certificate