



JUK Series

JUK 2.5B

Approval	CE 
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB6
Order Code	1010.000



JUK 2.5N

Approval	CE 
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB5
Order Code	1010.001



Technical Data

size	T6.2×H42×W42.5
rated current	32A
rated voltage	800V
solid cross section (min)	0.2mm ²
solid cross section (max)	4mm ²
stranded cross section (min)	0.2mm ²
stranded cross section (max)	2.5mm ²
packing	50
connection type	screw connection
Din Rail type	NS 35/7.5
	NS 35/15
	NS 32

size	T5.2×H42×W42.5
rated current	32A
rated voltage	800V
solid cross section (min)	0.2mm ²
solid cross section (max)	4mm ²
stranded cross section (min)	0.2mm ²
stranded cross section (max)	2.5mm ²
packing	50
connection type	screw connection
Din Rail type	NS 35/7.5
	NS 35/15
	NS 32

Accessories (P51-54)

(1) end cover	grey	D-JUK 2.5 B
(2) fixed bridge		FBI 10-6
(3) insertion bridge	poles, 2 poles 3 poles 10 poles	EB 2-6 EB 3-6 EB 10-6
(4) switching jumper	silver	
(5) separating plate	grey	TS-K
(6) partition plate	grey	ATP-JUK
(7) end clamp		E/JUK

(1) end cover		D-JUK 2.5 B
(2) fixed bridge		FBI 10-5
(3) insertion bridge		EB 2-5 EB 3-5 EB 10-5
(4) switching jumper		JUSBR 2-7
(5) separating plate		TS-K
(6) partition plate		ATP-JUK
(7) end clamp		E/JUK

Approval	CE
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB5
Order Code	1010.002

Approval	CE
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB6
Order Code	1010.003



Technical Data


	JUK 3N	JUK 5N
size	T6.2×H47×W42.5	T6.2×H47×W42.5
rated current	32A	41A
rated voltage	800V	800V
solid cross section (min)	0.2mm ²	0.2mm ²
solid cross section (max)	4mm ²	6mm ²
stranded cross section (min)	0.2mm ²	0.2mm ²
stranded cross section (max)	2.5mm ²	4mm ²
packing	50	50
connection type	screw connection	screw connection
Din Rail type	NS 35/7.5	NS 35/7.5
	NS 35/15	NS 35/15
	NS 32	NS 32

Accessories (P51-54)

	JUK 3N	JUK 5N
(1) end cover	grey D-JUK 4/10	D-JUK 4/10
(2) fixed bridge	FBI 10-5	FBI 10-6
(3) insertion bridge	poles: 2 poles 3 poles 10poles EB 2-5 EB 3-5 EB 10-5	EB 2-6 EB 3-6 EB 10-6
(4) switching jumper	silver	JUSBR 2-7
(5) separating plate	grey TS-K	TS-K
(6) partition plate	grey ATP-JUK	ATP-JUK
(7) end clamp	E/JUK	E/JUK


JUK Series

JUK 6N

Approval	CE 
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB8
Order Code	1010.004



JUK 10N

Approval	CE 
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB10
Order Code	1010.005



Technical Data

size	T8.2×H47×W42.5	T10.2×H47×W42.5
rated current	57A	76A
rated voltage	800V	800V
solid cross section (min)	0.2mm ²	0.5mm ²
solid cross section (max)	10mm ²	16mm ²
stranded cross section (min)	0.2mm ²	0.5mm ²
stranded cross section (max)	6mm ²	10mm ²
packing	50	50
connection type	screw connection	screw connection
	NS 35/7.5	NS 35/7.5
Din Rail type	NS 35/15	NS 35/15
	NS 32	NS 32

Accessories (P51-54)

(1) end cover	grey	D-JUK 4/10	D-JUK 4/10
(2) fixed bridge		FBI 10-8	FBI 10-10
(3) insertion bridge	poles: 2 poles 3 poles 10 poles	EB 2-8 EB 3-8 EB 10-8	EB 2-10 EB 3-10 EB 10-10
(4) switching jumper	silver	JUR 2-8/13	
(5) separating plate	grey	TS-K	TS-K
(6) partition plate	grey	ATP-JUK	ATP-JUK
(7) end clamp		E/JUK	E/JUK

JUK 16N

Approval	CE
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB10
Order Code	1010.006



JUK 16N

Approval	CE
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB10
Order Code	1010.008



JUK 35

Approval	CE
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB10
Order Code	1010.007



T12.2×H47×W42.5

101A
800V
2.5mm ²
25mm ²
4mm ²
16mm ²
50
screw connection
NS 35/7.5
NS 35/15
NS 32

T12.2×H54×W42.5

100A
800V
2.5mm ²
25mm ²
4mm ²
16mm ²
50
screw connection
NS 35/7.5
NS 35/15
NS 32

T15.2×H51×W55.5

125A
800V
10mm ²
35mm ²
10mm ²
35mm ²
50
screw connection
NS 35/7.5
NS 35/15
NS 32

D-JUK 16

FBI 10-12F
EB 2-12
EB 3-12
EB 10-12

TS-K

ATP-JUK

E/JUK

D-JUK 16

FBI 10-12
EB 2-15
EB 3-15
EB 10-15

TS-K

ATP-JUK

E/JUK

FBI 10-15


EB 2-15
EB 3-15
EB 10-15

TS-K

E/JUK


JUK Series

JUK 35N

Approval	CE 
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB10
Order Code	1010.009



JUKH 50

Approval	CE 
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB10
Order Code	1010.010



Technical Data

size	T15.2×H62×W55	T20×H83.5×W70.5
rated current	125A	150A
rated voltage	800V	1000V
solid cross section (min)	10mm ²	16mm ²
solid cross section (max)	35mm ²	50mm ²
stranded cross section (min)	10mm ²	25mm ²
stranded cross section (max)	35mm ²	50mm ²
packing	50	10
connection type	screw connection	screw connection
	NS 35/7.5	NS 35/7.5
Din Rail type	NS 35/15	NS 35/15
	NS 32	NS 32

Accessories (P51-54)

(1) end cover	grey	
(2) fixed bridge		FBI 2-15 / FBI 3-15
(3) insertion bridge	poles: 2 poles 3 poles 10poles	EB 2-15 EB 3-15 EB 10-15
(4) partition plate	grey	TS-K
(5) separating plate	grey	
(6) end clamp		E / AL-NS 35

JUKH 95

JUKH 150

JUKH 240

Approval	CE
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB10
Order Code	1010.011

Approval	CE
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB10
Order Code	1010.012

Approval	CE
Insulating Material	PA66
Inflammability Class	UL 94 V ₀
Connection Standard	IEC 60947-7-1
Zack Strip	ZB10
Order Code	



T25×H97.5×W83

232A

1000V

25mm²

95mm²

35mm²

95mm²

10

screw connection

NS 35/7.5

NS 35/15

NS 32

T31×H119×W100

309A

1000V

35mm²

150mm²

50mm²

150mm²

10

screw connection

NS 35/7.5

NS 35/15

NS 32

T36×H131.5×W100

415A

1000V

70mm²

240mm²

70mm²

240mm²

10

screw connection

NS 35/7.5

NS 35/15

NS 32

EB 2-35
EB 3-35

EB 2-31
EB 3-31

EB 2-36
EB 3-36

E / AL-NS 35

E / AL-NS 35

E / AL-NS 35