

















Φ 22 LA39-B series pushbutton selection

Name	Type	Working status	Order code	Color	Light voltage	Dimension
 <p>Note: Φ40、Φ60</p>	<p>Momentary</p> <p>Latching</p>	<p>LA39-B2- ■ M/ ▲</p> <p>LA39-B2- ■ MT/ ▲</p>	<p>Non-transparent</p> <p>● Red-r</p> <p>● Green-g</p> <p>● Yellow-y</p> <p>● Black-k</p>		 <p>Note: if the tolerance is not marked, follow GB/T 1804 – class c</p>	
 <p>Note: Φ40、Φ60</p>	<p>Momentary</p> <p>Latching</p>	<p>LA39-B2- ■ MD/ ▲★</p> <p>LA39-B2- ■ MTD/ ▲★</p>	<p>Transparent</p> <p>● Red-r</p> <p>● Green-g</p> <p>● Yellow-y</p> <p>○ White-w</p>	<p>LED light source:</p> <p>21-AC/DC 6V</p> <p>22-AC/DC 12V</p> <p>23-AC/DC 24V</p> <p>24-AC/DC 36V</p> <p>25-AC/DC 48V</p> <p>26-AC/DC 110V</p> <p>27-AC/DC 127V</p> <p>28-AC/DC 220V</p> <p>33-AC/DC 270V</p> <p>35-AC/DC 440V</p> <p>31-AC 220V</p> <p>40-AC 230V</p> <p>32-AC 380V</p>	 <p>Note: if the tolerance is not marked, follow GB/T 1804 – class c</p>	
 <p>Note: Φ40</p> <p>Note: Φ40、Φ60</p>	<p>Latching by pressing, resetting by rotating clockwise</p>	<p>LA39-B2-R ■ Z/ ▲</p> <p>LA39-B2-R ■ Z1/ ▲</p>	<p>Non-transparent</p> <p>● Red-r</p>		 <p>Note: if the tolerance is not marked, follow GB/T 1804 – class c</p>	
 <p>Note: Φ40</p>	<p>Latching by pressing, resetting by rotating the key clockwise</p>	<p>LA39-B2-R ■ ZY/ ▲</p>			 <p>Note: if the tolerance is not marked, follow GB/T 1804 – class c</p>	

Note

- Indicate the number of NO/NC contacts at ■ before the slash, indicate the color at ▲ behind the slash and indicate the voltage grade of illuminated button at .
 - The light sources of illuminated buttons are high brightness LED in pure color.
 - If Z1, Z3, Z4 and Z5 middle seats are required during order, change B2 in the order code to B1, B3, B4 or B5.
 - The finished latching button is equipped with F5 accessory.
- Note: if Φ 60 mushroom head is required, please mark “-60” behind the order code, no marking for Φ 40 ones.
- The emergency stop button adopts slow-action base.

Φ 22 LA39-B series pushbutton selection

Name	Type	Working status	Order code	Color	Light voltage	Dimension
 <p>Note: Φ40、Φ60</p>	Momentary		LA39-B2- ■ M/ ▲	Non-transparent		 <p>Note: if the tolerance is not marked, follow GB/T 1804 – class c</p>
	Latching		LA39-B2- ■ MT/ ▲	<ul style="list-style-type: none"> ● Red-r ● Green-g ● Yellow-y ● Black-k 		
 <p>Note: Φ40、Φ60</p>	Momentary		LA39-B2- ■ MD/ ▲★	Transparent	LED light source: 21-AC/DC 6V 22-AC/DC 12V 23-AC/DC 24V 24-AC/DC 36V 25-AC/DC 48V 26-AC/DC 110V 27-AC/DC 127V 28-AC/DC 220V 33-AC/DC 270V 35-AC/DC 440V 31-AC 220V 40-AC 230V 32-AC 380V	 <p>Note: if the tolerance is not marked, follow GB/T 1804 – class c</p>
	Latching		LA39-B2- ■ MTD/ ▲★	<ul style="list-style-type: none"> ● Red-r ● Green-g ● Yellow-y ○ White-w 		
 <p>Note: Φ40、Φ60</p>	Latching by pressing, resetting by rotating clockwise		LA39-B2-R ■ Z/ ▲	Non-transparent		 <p>Note: if the tolerance is not marked, follow GB/T 1804 – class c</p>
			LA39-B2-R ■ Z1/ ▲			
 <p>Note: Φ40</p>	Latching by pressing, resetting by rotating the key clockwise		LA39-B2-R ■ ZY/ ▲			 <p>Note: if the tolerance is not marked, follow GB/T 1804 – class c</p>

Note

- Indicate the number of NO/NC contacts at ■ before the slash, indicate the color at ▲ behind the slash and indicate the voltage grade of illuminated button at .
 - The light sources of illuminated buttons are high brightness LED in pure color.
 - If Z1, Z3, Z4 and Z5 middle seats are required during order, change B2 in the order code to B1, B3, B4 or B5.
 - The finished latching button is equipped with F5 accessory.
- Note: if Φ 60 mushroom head is required, please mark “-60” behind the order code, no marking for Φ 40 ones.
The emergency stop button adopts slow-action base.