


Connection accessories (Cu or Al)				
Rear connections				
DB112225		2 short 2 long		LV432475 LV432476
Cable connectors⁽¹⁾				
E22040		Aluminium connector 1x (35 to 300 mm ²)	Set of 3 Set of 4	LV432479 LV432480
E22041		Aluminium connector 2x (35 to 240 mm ²)	Set of 3 Set of 4	LV432481 LV432482
		Voltage plug for aluminium connector 1 or 2 cables	Set of 10	LV429348
Terminal extension⁽¹⁾				
E21012		Spreaders	52.5 mm 70 mm	3P 4P 3P 4P
				LV432490 LV432491 LV432492 LV432493
Insulation accessories				
E18618		Short terminal shield, 45 mm (1 piece)	3P 4P	LV432591 LV432592
		Long terminal shield, 45 mm (1 piece)	3P 4P	LV432593 LV432594
E18606		Interphase barriers Long terminal shield for spreaders, 52,5mm (1 piece) (supplied with insulating plate)	Set of 6 3P 4P	LV432570 LV432595 LV432596
		2 insulating screens (70 mm pitch)	3P 4P	LV432578 LV432579
(1) supplied with 2 or 3 interphase barriers				
Electrical auxiliaries				
Auxiliary contacts (changeover)				
E18608		OF or SD or SDE or SDV OF or SD or SDE or SDV low level		29450 29452
Voltage releases				
		Voltage	MX	MN
	AC	110-130 V 50/60 Hz 220-240 V 50/60 Hz and 208-277 V 60 Hz 380-415 V 50 Hz and 440-480 V 60 Hz	LV429386 LV429387 LV429388	LV429406 LV429407 LV429408
	DC	Voltage 24 V	LV429390	LV429410