






LN12N ĐM 170/12W

PHÂN BỐ QUANG




LƯỚI ĐỘ RỌI





LN12N ĐM 170x170/12W

PHÂN BỐ QUANG




LƯỚI ĐỘ RỌI




Model	Công suất	Dải điện áp hoạt động	Tần số	Quang thông	Nhiệt độ màu	Chỉ số hoàn màu	Tuổi thọ	Kích thước
	W	V	Hz	lm	K		giờ	mm
LN12N ĐM 170/12W	12	150÷250	50	900/810/900	6500/3000/4000	80	25.000	160x41
LN12N ĐM 170x170/12W	12	150÷250	50	900/810/900	6500/3000/4000	80	25.000	160x160x41

BỘ ĐÈN M26 ĐỔI MÀU






M26 ĐM 1200/40W


PHÂN BỐ QUANG



LƯỚI ĐỘ RỌI




BỘ ĐÈN M36 ĐỔI MÀU






M36 ĐM 1200/40W

PHÂN BỐ QUANG



LƯỚI ĐỘ RỌI



Model	Công suất	Dải điện áp hoạt động	Tần số	Hệ số công suất	Hiệu suất sáng	Quang thông	Nhiệt độ màu	Chỉ số hoàn màu	Tuổi thọ	Kích thước
	W	V	Hz		lm/W	lm			giờ	mm
M26 ĐM 1200/40W	40	150÷250	50	0.5	117/130	4400/3960/4400	6500/3000/4000	80	25000	1200x75x25
M36 ĐM 1200/40W	40	150÷250	50	0.5	100/110	4400/4000/4400	6500/3000/4000	80	30000	1.172x61x31