




LED RECESSED DOWNLIGHT OLA Series











Note:

- Published lumen is total luminous flux of luminaire



≥0.8	80Ra	IP20	25,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features

-  Bridgelux/Epistar
-  Flicker-free
-  Low glare
-  High quality material and exceptional energy saving performance
-  High quality aluminium alloy heatsink
-  3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
-  No UV radiation
-  No mercury, environmentally friendly

SPECIFICATION AND PRICE

Model	OLA16L6	OLA26L12	OLA36L18	OLA46L24
LED chip	Bridgelux/Epistar			
Wattage (W)	1x6W	2x6W	3x6W	4x6W
Efficacy (Lm/W)	75	75	75	75
Lumen (Lm)	450	900	1350	1800
Color temperature (K)	3000/4200/6500			
Dimensions (mm) (LxWxH)	110x110x110	216x110x110	300x110x110	385x110x110
Ceiling cut-out (mm)	90x90	195x90	277x90	365x90
Unit price (USD)	\$25.91	\$47.39	\$66.00	\$86.74

Suggested installation areas



Apartment



Supermarket



Retail Store



Office



Hotel



School



Hospital