




LED SLIM DOWNLIGHT PDPA Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.5
- Lifespan: 25,000 hours
- CRI ≥ 80

≥ 0.5	80Ra	Ip44	25,000 Hours	Ac100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features

- Bridgelux/Samsung
- High quality PC diffuser cover
- Optical plate from Japan
- Even distribution of light
- Ultra-slim design
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Compatible with Emergency Backup Battery
- Minimise blue light emission

SPECIFICATION AND PRICE

Model	PDPA97L7	PDPA122L9	PDPA162L12	PDPA167L18
LED chip	Bridgelux/Samsung			
Wattage (W)	7W	9W	12W	18W
Efficacy (Lm/W)	80	90	92	95
Lumen (Lm)	576	815	1111	1761
Color temperature (K)	3000/4200/6500			
Dimensions (mm) (WxH)	97x27	122x27	162x29	167x29
Ceiling cut-out (mm)	82-90	107-115	147-155	152-160
Unit price (USD)	\$9.48	\$10.35	\$14.17	\$22.35

Suggested installation areas

