




**LED HIBAY
PHBEE Series**



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 80

| | | | | | |
|--------------|------|------------------|--------------|------------|-----------|
| ≥ 0.9 | 80Ra | IP65 | 50,000 Hours | AC100 240V | 50-60Hz |
| Power factor | CRI | Protection grade | Lifespan | Voltage | Frequency |

Outstanding features

- Osram/Nichia
- Flicker-free
- No UV radiation
- High quality aluminium alloy heat sink
- Energy saving
- Adjustable brightness
- Easy installation and maintenance
- No mercury, environmentally friendly

SPECIFICATION AND PRICE

| Model | PHBEE100L | PHBEE120L | PHBEE150L |
|--------------------------|-----------------|-----------------|-----------------|
| LED chip | Osram/Nichia | | |
| Wattage (W) | 100W | 120W | 150W |
| Efficacy (Lm/W) | 105 | 105 | 105 |
| Lumen (Lm) | 10500 | 12600 | 15750 |
| Color temperature (K) | 4500~5500 | | |
| Dimensions (mm) (WxH) | 358x265 | 358x265 | 358x265 |
| Installation | Suspended | | |
| Unit price (USD) | \$285.35 | \$305.65 | \$328.83 |

Suggested installation areas

