




LED HIBAY PHBSS Series



Note:

- Efficacy: 100Lm/W
- PF ≥ 0.9
- Lifespan: 30,000 Hours
- CRI ≥ 80

≥ 0.9	80Ra	IP65	30,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features

- Bridgelux/Seoul
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Energy saving
- High quality aluminium alloy heatsink
- No UV radiation
- No mercury, environmentally friendly
- Easy installation and maintenance
- 20 - 50°C

SPECIFICATION AND PRICE

Model	PHBSS60L	PHBSS100L	PHBSS150L	PHBSS200L
LED chip	Bridgelux/Seoul			
Wattage (W)	60W	100W	150W	200W
Efficacy (Lm/W)	150	150	150	150
Lumen (Lm)	9000	15000	22500	30000
Color temperature (K)	3000/4200/6500			
Dimensions (mm) (WxH)	280x113	330x126	380x130	380x150
Installation	Suspended			
Unit price (USD)	\$82.00	\$96.57	\$138.09	\$172.52

Suggested installation areas



Public areas



Supermarket



Factory



Parking lot



Warehouse



School



Hospital