





LED



RECESSED LINEAR LUMINAIRE PHLM Series




≥0.9 Power factor	80Ra CRI	IP20 Protection grade	25,000 Hours Lifespan	AC220-240V Voltage	50-60Hz Frequency
----------------------	-------------	--------------------------	--------------------------	-----------------------	----------------------

Outstanding features

- Bridgelux/Epistar
- High quality aluminium alloy heat sink
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Tunable white - 3000K-6500K
- RGB color function (*)
- Low glare
- No UV radiation
- Minimise blue light emission

SPECIFICATION AND PRICE

Model	PHLM10L	PHLM20L
LED chip	Bridgelux/Epistar	
Efficacy (Lm/W)	80	80
Lumen (Lm)	800	1600
Color temperature (K)	3000/4200/6500	
Wattage (W)	10W±1	20W±2
Lifespan (hrs)	25,000	
Dimensions (mm)	580x35x64.8	1200x35x64.8
Unit price (USD)	\$26.74	\$52.26



PHLM001: \$2.17 PHLM002: \$2.17 PHLM003: \$2.17

Suggested installation areas



(*) Available upon request

- Customizable dimensions and adjustable colour temperature are available upon request