




OUTDOOR FLOODLIGHT (HIGH MAST) PHMA Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 70

≥ 0.9	70Ra	IP65	50,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features



Nichia/Osram



High quality aluminium alloy heat sink



Energy saving



No mercury, environmentally friendly



Diverse beam angle available: 15, 30, 60x90°



Electrical safety assurance



Easy installation and maintenance



Perfect replacement for high pressure sodium and metal halide lamps

SPECIFICATION AND PRICE

Model	PHMA30065L	PHMA60065L	PHMA90065L
LED chip	Nichia/Osram		
Wattage (W)	300W	600W	900W
Efficacy (Lm/W)	125	125	125
Lumen (Lm)	37500	75000	112500
Color temperature (K)	4500~5500		
Dimensions (mm) (LxWxH)	320x485x93	554x498x110	554x715x110
Operating temperature	-30~50°C		
Unit price (USD)	\$887.26	\$2,044.91	\$3,050.48

Suggested installation areas



Public areas



Advertising board



Sports complex



Parking lot



Landscape & facade



Airport



Wharf