




LED



OUTDOOR FLOODLIGHT POLH Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 70

≥ 0.9	70Ra	IP65	50,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features

- Bridgelux/Epistar
- High quality aluminium alloy heat sink
- Energy saving
- No mercury, environmentally friendly
- Dustproof & water-resistant
- Electrical safety assurance
- Easy installation and maintenance
- Perfect replacement for high pressure sodium and metal halide lamps

SPECIFICATION AND PRICE

Model	POLH1065	POLH2065	POLH3065	POLH5065	POLH8065
LED chip	Bridgelux/Epistar				
Wattage (W)	10W	20W	30W	50W	80W
Efficacy (Lm/W)	100	100	100	100	100
Lumen (Lm)	1000	2000	3000	5000	8000
Color temperature (K)	3000/4200/6500				
Dimensions (mm) (LxWxH)	113x85x80	178x140x110	230x182x125	285x230x145	285x360x115
Operating temperature	-30~50°C				
Unit price (USD)	\$21.17	\$38.78	\$56.39	\$86.09	\$152.57

Suggested installation areas



Public areas



Advertising board



Residential area



Parking lot



Landscape & facade



Parks & gardens



Apartment