




OUTDOOR FLOODLIGHT POLT Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 80

≥ 0.9	80Ra	IP65	50,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features



Bridgelux/Epistar



High quality aluminium alloy heat sink



Energy saving



No mercury, environmentally friendly



Dustproof & water-resistant



Electrical safety assurance



Easy installation and maintenance



Perfect replacement for high pressure sodium and metal halide lamps

SPECIFICATION AND PRICE

Model	POLT565L	POLT1065L	POLT2065L
LED chip	Bridgelux/Epistar		
Wattage (W)	5W	10W	20W
Efficacy (Lm/W)	80	80	80
Lumen (Lm)	400	800	1600
Color temperature (K)	3000/4200/6500		
Dimensions (mm) (LxW)	110x120	115x170	150x210
Operating temperature	-30~50°C		
Unit price (USD)	\$51.70	\$68.09	\$98.74

Suggested installation areas



Public areas



Advertising board



Residential area



Parking lot



Landscape & facade



Parks & gardens



Apartment