




To cycle through between different color temperature, toggle light switch from on-off-on within 3 seconds.



LED RECESSED DOWNLIGHT PRDNN Series



≥0.5 Power factor	80Ra CRI	IP20 Protection grade	25,000 Hours Lifespan	AC100 240V Voltage	50-60Hz Frequency
----------------------	-------------	--------------------------	-----------------------------	--------------------------	----------------------

Outstanding features

- Bridgelux/Samsung
- High quality PC diffuser cover
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Compatible with Emergency Backup Battery
- No mercury, environmentally friendly
- High quality material and exceptional energy saving performance
- Easy installation and maintenance
- Energy saving

SPECIFICATION AND PRICE

(Luminaire is able to emit different color temperature when toggling switch from On-Off-On)

Model	PRDNN104L7/CCT	PRDNN104L9/CCT	PRDNN157L12/CCT
LED chip	Bridgelux/Samsung		
Wattage (W)	7W	9W	12W
Efficacy (Lm/W)	85	85	110
Lumen (Lm)	595	765	1320
Color temperature (K)	3000/4200/6500		
Dimensions (mm) (WxH)	104x104	104x104	157x157
Ceiling cut-out (mm)	90x90	90x90	145x145
Unit price (USD)	\$14.17	\$15.70	\$20.26

Suggested installation areas

