




To cycle through between different color temperature, toggle light switch from on-off-on within 3 seconds.



LED



LED RECESSED DOWNLIGHT PRDPP Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.5
- Lifespan: 25,000 hours
- CRI ≥ 80

≥0.5	80Ra	IP20	25,000 Hours	AC100-240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features

- Bridgelux/Samsung
- High quality PC diffuser cover
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Compatible with Emergency Backup Battery
- Flicker-free
- High quality material and exceptional energy saving performance
- Low glare
- Energy saving

SPECIFICATION AND PRICE

(Luminaire is able to emit different color temperature when toggling switch from On-Off-On)

Model	PRDPP104L7/CCT	PRDPP104L9/CCT	PRDPP157L12/CCT
LED chip	Bridgelux/Samsung		
Wattage (W)	7W	9W	12W
Efficacy (Lm/W)	85	85	110
Lumen (Lm)	565	765	1320
Color temperature (K)	3000/4200/6500		
Dimensions (mm) (WxW)	104x104	104x104	157x157
Ceiling cut-out (mm)	90x90	90x90	145x145
Unit price (USD)	\$15.43	\$17.30	\$21.61

Suggested installation areas

