




RECESSED REFLECTIVE LUMINAIRE PRFF Series



(For gypsum and wood false ceiling installation)



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 80

≥ 0.9	80Ra	IP20	50,000 Hours	AC220 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features

- LED chip from Bridgelux/Epistar
- Pre-anodized aluminium reflector
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Lamp holder and accessories by BJB - Germany
- Compatible with Emergency Backup Battery
- Low glare
- Easy installation and maintenance
- Energy saving

SPECIFICATION AND PRICE

Model	PRFF218L20	PRFF318L30	PRFF418L40	PRFF236L36	PRFF336L54	PRFF436L72
Lamp type	2x10W	3x10W	4x10W	2x20W	3x20W	4x20W
Efficacy (Lm/W)	80	80	80	80	80	80
Lumen (Lm)	1600	2400	3200	3200	4800	6400
Color temperature (K)	3000/4200/6500					
Wattage (W)	20W \pm 2	30W \pm 3	40W \pm 4	40W \pm 4	60W \pm 6	80W \pm 8
Operating temperature	-20~40°C					
Dimensions (mm) (LxWxH)	640x314x90	640x634x90	640x634x90	1260x334x90	1260x634x90	1260x634x90
Unit price (USD)	\$40.52	\$60.57	\$75.00	\$61.78	\$91.39	\$117.30
Ceiling cut-out	615x280	615x580	615x580	1225x280	1225x580	1225x580

Suggested installation areas



- Unit price includes LED tube
(10W-1250lm, 20W-2500lm, PF>0.9, Lifespan 50,000 hours)