


RECESSED REFLECTIVE LUMINAIRE (T-bar) **PRFJ Series**





Note:

- Published lumen is total luminous flux of luminaire
- PF ≥0.9
- Lifespan: 50,000 hours
- CRI ≥80

≥0.9 80Ra Power factor

IP20

50,000 Hours Lifespan AC220 240V Voltage

50-60Hz Frequency

Outstanding features

LED chip from Bridgelux/Epistar



Stainless steel and aluminium strip reflector



3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)



Lamp holder and accessories by BJB - Germany



Compatible with Emergency Backup Battery



Low glare



Easy installation and maintenance



Minimise blue light emission

SPECIFICATION AND PRICE

Model	PRFJ218L20	PRFJ318L30	PRFJ418L40	PRFJ236L36	PRFJ336L54	PRFJ436L72
Lamp type	2x10W	3x10W	4x10W	2x20W	3x20W	4x20W
Efficacy (Lm/W)	60	60	60	60	60	60
Lumen (Lm)	1200	1800	2400	2400	3600	4800
Color temperature (K)	3000/4200/6500					
Wattage (W)	20W±2	30W±3	40W±4	40W±4	60W±6	80W±8
Operating temperature	-20~40°C					
Dimensions (mm)	606x302x88	606x606x88	606x606x88	1216x302x88	1216x606x88	1216x606x88
Unit price (USD)	\$31.83	\$47.87	\$60.74	\$43.87	\$69.13	\$83.91

Suggested installation areas















- Unit price includes LED tube (10W-1250lm, 20W-2500lm, PF>0.9, Lifespan 50,000 hours)