




**LED**



## LED RECESSED DOWNLIGHT PRHE Series



### Note:

- Published lumen is total luminous flux of luminaire
- PF  $\geq 0.9$
- Lifespan: 50,000 hours
- CRI  $\geq 80$

$\geq 0.9$	80Ra	IP44	50,000 Hours	AC100-240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

### Outstanding features

- Cree/Bridgelux
- Beam angle: 10°, 23°, 36°
- Low glare
- Adjustable brightness (Available upon request)
- High quality aluminium alloy heatsink
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Compatible with Emergency Backup Battery
- Flicker-free

## SPECIFICATION AND PRICE

Model	PRHE90L3	PRHE90L5	PRHE90L7	PRHE90L12
LED chip	Cree/Bridgelux			
Wattage (W)	3W	5W	7W	12W
Efficacy (Lm/W)	60	60	60	60
Lumen (Lm)	180	300	420	720
Color temperature (K)	3000/4200/6500			
Dimensions (mm) (WxH)	90x65	90x75	90x88	90x108
Ceiling cut-out (mm)	80	80	80	80
Unit price (USD)	<b>\$12.39</b>	<b>\$12.91</b>	<b>\$13.83</b>	<b>\$21.57</b>

### Suggested installation areas



Apartment



Supermarket



Retail Store



Office



Hotel



School



Hospital

CCT 2700K and compatibility with Triac, Dali, 1-10V dimmers are available upon request.