




LED



LED RECESSED DOWNLIGHT PRHH Series



≥0.9 Power factor	80Ra CRI	IP44 Protection grade	50,000 Hours Lifespan	AC100-240V Voltage	50-60Hz Frequency
----------------------	-------------	--------------------------	--------------------------	-----------------------	----------------------


Outstanding features

- Cree/Bridgelux
- Beam angle: 10°, 23°, 36°
- Low glare
- High quality material and exceptional energy saving performance
- No UV radiation
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Compatible with Emergency Backup Battery
- Energy saving

SPECIFICATION AND PRICE

Model	PRHH90L3	PRHH90L5	PRHH90L7	PRHH90L12
LED chip	Cree/Bridgelux			
Wattage (W)	3W	5W	7W	12W
Efficacy (Lm/W)	60	60	60	60
Lumen (Lm)	180	300	420	720
Color temperature (K)	3000/4200/6500			
Dimensions (mm) (WxH)	90x65	90x75	90x88	90x108
Ceiling cut-out (mm)	80x80	80x80	80x80	80x80
Unit price (USD)	\$12.39	\$12.91	\$13.83	\$21.57

Suggested installation areas



CCT 2700K and compatibility with Triac, Dali, 1-10V dimmers are available upon request.