




LED



LED RECESSED DOWNLIGHT PRHK Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 80

≥0.9	80Ra	IP44	50,000 Hours	AC100-240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features

- Cree/Bridgelux
- Beam angle: 10°, 23°, 36°
- Low glare
- Adjustable brightness (Available upon request)
- Energy saving
- 3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)
- Compatible with Emergency Backup Battery
- Easy installation and maintenance

SPECIFICATION AND PRICE

Model	PRHK90L3	PRHK90L5	PRHK90L7	PRHK90L12
LED chip	Cree/Bridgelux			
Wattage (W)	3W	5W	7W	12W
Efficacy (Lm/W)	60	60	60	60
Lumen (Lm)	180	300	420	720
Color temperature (K)	3000/4200/6500			
Dimensions (mm) (WxH)	90x65	90x75	90x88	90x108
Ceiling cut-out (mm)	80	80	80	80
Unit price (USD)	\$12.39	\$12.91	\$13.83	\$21.57

Suggested installation areas



Apartment



Supermarket



Retail Store



Office



Hotel



School



Hospital

CCT 2700K and compatibility with Triac, Dali, 1-10V dimmers are available upon request.