ETHOS®
A rationale of our own

TOP PLATE FITTING 660 PRZ

In Compliance to Japanese Standard Specification **SERIES** 120 - 400 KGS

Castor

660
Bracket made of heavy gauged steel
Metal parts: Electro-galvanized finished

Wheel

PRZ Polybutadiene elastic rubber
Inserted ball bearing for resilience and long-lasting lubrication
Hardness: 72± Elastic rubber interlocked to heavy gauged steel-core
Medium duty industrial usage. Temperature range -5°C to +80°C

	mm	mm	mm	mm	mm	mm	mm	mm	mm		kgs
661 PRZ 075 J01	82x82	63x63	9.5	101	22	75	32	10	35	✱✱	120
661 PRZ 100 J01	95x95	71x71	10.5	144	35	100	35	12	38	✱✱	160
661 PRZ 130 J01	108x108	80x80	11	177	40	130	38	20	52	✱✱	240
661 PRZ 150 J01	120x120	90x90	11	198	45	150	45	20	55	✱✱	270
661 PRZ 200 J01	140x140	112x112	11.5	250	58	200	45	20	55	✱✱	350
661 PRZ 250 J01	160x160	125x125	14	305	71	250	50	25	62	✱✱	400
662 PRZ 075 K02	95x72	63x40	9.5	101	-	75	32	10	35	✱✱	120
662 PRZ 100 K02	115x80	80x45	10.5	144	-	100	35	12	38	✱✱	160
662 PRZ 130 K02	137x93	100x56	11	177	-	130	38	20	52	✱✱	240
662 PRZ 150 K02	137x93	100x56	11	198	-	150	45	20	55	✱✱	270
662 PRZ 200 K02	155x102	112x63	11.5	250	-	200	45	20	55	✱✱	350
662 PRZ 250 K02	200x140	140x80	14	305	-	250	50	25	62	✱✱	400
663 PRZ 075 JB1	82x82	63x63	9.5	101	22	75	32	10	35	✱✱	120
663 PRZ 100 JB1	95x95	71x71	10.5	144	35	100	35	12	38	✱✱	160
663 PRZ 130 JB1	108x108	80x80	11	177	40	130	38	20	52	✱✱	240
663 PRZ 150 JB1	120x120	90x90	11	198	45	150	45	20	55	✱✱	270
663 PRZ 200 JB1	140x140	112x112	11.5	250	58	200	45	20	55	✱✱	350
663 PRZ 250 JB1	160x160	125x125	14	305	71	250	50	25	62	✱✱	400

	mm	mm	mm	mm	✱✱	kgs
PRZ 075x32	75	32	10	35	✱✱	120
PRZ 100x35	100	35	12	38	✱✱	160
PRZ 130x38	130	38	20	52	✱✱	240
PRZ 150x45	150	45	20	55	✱✱	270
PRZ 200x45	200	45	20	55	✱✱	350
PRZ 250x50	250	50	25	62	✱✱	400