




LED SURFACE DOWNLIGHT PSDOO Series



Note:

- Published lumen is total luminous flux of luminaire
- PF ≥ 0.9
- Lifespan: 50,000 hours
- CRI ≥ 80

≥ 0.9	80Ra	IP20	50,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

Outstanding features



Bridgelux/Nichia



Pre-anodized aluminium reflector



3000K(Warm white) / 4200K(Neutral white) / 6500K(Cool daylight)



No UV radiation



Flicker-free



High quality material and exceptional energy saving performance



Low glare



Energy saving

SPECIFICATION AND PRICE

Model	PSDOO132L10	PSDOO170L20	PSDOO196L25	PSDOO230L30
LED chip	Bridgelux/Nichia			
Wattage (W)	10W	20W	25W	30W
Efficacy (Lm/W)	100	100	100	100
Lumen (Lm)	1000	2000	2500	3000
Color temperature (K)	3000/4200/6500			
Dimensions (mm) (WxH)	132x155	170x195	196x199	230x220
Installation	Surface			
Unit price (USD)	\$31.00	\$53.52	\$71.83	\$95.74

Suggested installation areas



Apartment



Supermarket



Retail Store



Office



Hotel



School



Hospital