



## FACADE LUMINAIRE

Model	PWWA18L-24	PWWA18L/RGB	PWWA18L
LED chip	Bridgelux/Epistar		
Wattage (W)	18W	18W	18W
Efficacy (Lm/W)	65	35	65
Lumen (Lm)	1170	630	1170
Color temperature (K)	3000/4200/6500	RGB	3000/4200/6500
Dimensions (mm) (LxWxH)	1000x45x27.5	1000x34x53	1000x45x27.5
Voltage (V)	24	24	220-240
Unit price (USD)	<b>\$85.43</b>	<b>\$129.57</b>	<b>\$114.52</b>

## FACADE LUMINAIRE

Model	PWWA24L-24	PWWA24L/RGB	PWWA24L
LED chip	Bridgelux/Epistar		
Wattage (W)	24W	24W	24W
Efficacy (Lm/W)	65	35	65
Lumen (Lm)	1560	840	1560
Color temperature (K)	3000/4200/6500	RGB	3000/4200/6500
Dimensions (mm) (LxWxH)	1000x45x27.5	1000x34x53	1000x45x27.5
Voltage (V)	24	24	220-240
Unit price (USD)	<b>\$90.57</b>	<b>\$136.78</b>	<b>\$119.70</b>

Note: Unit price does not include 24V transformer

