



## FACADE LUMINAIRE

Model	PWWA30L-24	PWWA30L/RGB	PWWA30L
LED chip	Bridgelux/Epistar		
Wattage (W)	30W	30W	30W
Efficacy (Lm/W)	65	35	65
Lumen (Lm)	1950	1050	1950
Color temperature (K)	3000/4200/6500	RGB	3000/4200/6500
Dimensions (mm) (LxWxH)	1000x45x27.5	1000x34x53	1000x45x27.5
Voltage (V)	24	24	220-240
Unit price (USD)	<b>\$123.57</b>	<b>\$165.57</b>	<b>\$152.70</b>

## FACADE LUMINAIRE

Model	PWWA36L-24	PWWA36L/RGB	PWWA36L
LED chip	Bridgelux/Epistar		
Wattage (W)	36W	36W	36W
Efficacy (Lm/W)	65	35	65
Lumen (Lm)	2340	1260	2340
Color temperature (K)	3000/4200/6500	RGB	3000/4200/6500
Dimensions (mm) (LxWxH)	1000x34x53	1000x34x53	1000x34x53
Voltage (V)	24	24	220-240
Unit price (USD)	<b>\$129.35</b>	<b>\$172.74</b>	<b>\$158.52</b>

Note: Unit price does not include 24V transformer



**LED**

