


QTC50L

Ø50mm LED Steady/Flashing Tower Lights

Qlightec



QTC50L series



QTCA50L series

• Customization



- High buzzer module equipped on top/ Black housing tower lights.

QTC50L Ø50mm Pole Mount, LED Steady/Flashing Type

| Model number | Layer | Voltage | Current | Certificates | Weight | Color | | | | |
|--|-------|-------------|-------------|--------------------|--------------------|--------------------|----------------------|-----------------------------------|---|--|
| QTC50L Steady | 1 | AC/DC12V | 0.085A | DC24V only | 0.35kg | • R-Red | | | | |
| QTC50L-BZ Steady /w built-in buzzer | | AC/DC24V | 0.065A | | 0.35kg | | | | | |
| QTC50LF Steady/Flashing | | AC110V-220V | Max. 0.045A | | 0.45kg | | | | | |
| QTC50L-BZ Steady/Flashing /w built-in buzzer | 2 | AC/DC12V | 0.170A | | DC24V only | 0.44kg | • R-Red • G-Green | | | |
| QTC50LF Steady/Flashing | | AC/DC24V | 0.130A | | | 0.44kg | | | | |
| QTC50LF-BZ Steady/Flashing /w built-in buzzer | | AC110V-220V | Max. 0.065A | | | 0.54kg | | | | |
| QTCA50L Steady | 3 | AC/DC12V | 0.255A | | | DC24V only | 0.52kg | • R-Red • A-Amber • G-Green | | |
| QTCA50L-BZ Steady /w built-in buzzer | | AC/DC24V | 0.195A | | | | 0.52kg | | | |
| QTCA50LF Steady/Flashing | | AC110V-220V | Max. 0.085A | | | | 0.62kg | | | |
| QTCA50L-BZ Steady /w built-in buzzer | 4 | AC/DC12V | 0.340A | | | | DC24V only | 0.61kg | • R-Red • A-Amber • G-Green • B-Blue | |
| QTCA50LF Steady/Flashing | | AC/DC24V | 0.260A | | | | | 0.61kg | | |
| QTCA50LF-BZ Steady/Flashing /w built-in buzzer | | AC110V-220V | Max. 0.105A | | | | | 0.71kg | | |
| QTCA50LF-BZ Steady/Flashing /w built-in buzzer | 5 | AC/DC12V | 0.425A | | | | | DC24V only | 0.69kg | • R-Red • A-Amber • G-Green • B-Blue • W-White |
| QTCA50LF Steady/Flashing | | AC/DC24V | 0.325A | | | | | | 0.69kg | |
| QTCA50LF-BZ Steady/Flashing /w built-in buzzer | | AC110V-220V | Max. 0.125A | | | | | | 0.79kg | |

* AC type model has a free-voltage range of 100V-240V.

Wiring Instructions

- External power line standard : UL1015 AWG18(0.75sq)×2C 400mm
- Signal line standard : UL1007 AWG22(0.3sq) 400mm
- LED tower light can be wiring with external contact and transistor

* Please refer to page 331-332 for detailed wiring instructions.

Mounting Bracket

| Standard | LB18 | LW18 | QZ18 | SZ18 | QL18 | SL18 | QLA18 |
|----------|-------|------|------|------|------|------|-------|
| | | | | | | | |
| Steel | Steel | PC | PC | Al | PC | Al | PC |

* Please refer to page 34-39 for detailed dimensions.

Customization

- 2 buzzer sound types : Both prolonged (beep, beep) and staccato (beep, beep) buzzer output available
- Customized pole length available
- High buzzer module equipped on top(Lens should be within 4 layers)
- Black housing tower lights

Ordering Specification

| QTC50L | - | 3 | - | 24 | - | RAG | - | LW18 |
|----------------|---|-------------|---|--------------|---|-----------|---|--------------------|
| [Model number] | | [Layer] | | [Voltage] | | [Color] | | [Mounting bracket] |
| • QTC50L | | • 1-1Layer | | • 12-DC12V | | • R-Red | | • None |
| • QTC50L-BZ | | • 2-2Layers | | • 24-DC24V | | • A-Amber | | • -Standard |
| • QTC50LF | | • 3-3Layers | | • 110/220 | | • G-Green | | • Bracket |
| • QTC50LF-BZ | | • 4-4Layers | | -AC110V-220V | | • B-Blue | | -LB18 -LW18 |
| • QTCA50L | | • 5-5Layers | | | | • W-White | | -QZ18 -SZ18 |
| • QTCA50L-BZ | | | | | | | | -QL18 -SL18 |
| • QTCA50LF | | | | | | | | -QLA18 |
| • QTCA50LF-BZ | | | | | | | | |