QWH series

Wall mount electric horn that offers 31 pre-recorded warning sounds and 30 user selected sound messages

- Bit input offers 5 channels with 6 sound outputs
- Binary input offers 31 sound outputs and SD Card (MP3) combination

Sound Selection and Volume Adjustment Instructions

QWH series has control switches inside the unit for sound selection and volume adjustment. You can play customized sound message(MP3) with SD Card.

QWH series Product Category

QWH35	Standard pre-recorded sound type
QWH35SD	SD Card(MP3) type
QWH50	Standard pre-recorded sound type with high volume output
QWH50SD	SD Card (MP3)type with high volume output

Pre-recorded sound type



Switch for channel selection

2 Switch for volume adjustment

SD Card (MP3) type



Switch for sound pattern selection

- 2 SD Card slot for MP3
- 3 Switch for play mode selection
- 4 Switch for channel selection
- 5 Switch for volume adjustment



Qight

① Common Specifications(QWH35/ QWH35SD/ QWH50/ QWH50SD)

- Signal fit for the specific environment and condition.
- Options to select between 31 special warning sounds included in the pre-recorded sound type and SD Card(MP3) type
- Volume adjustment and sound selection switches located inside the unit. SD Card in the unit offers convenient operation.
- SD Card type allows the user to input the proper voice messages for specific operating conditions.
- The SD Card type 31 Special alarms built in which includes the voice alert from the SD Card (MP3). 31 special warning sounds are built both in pre-recorded sound type and SD Card type
- Offers both Binary and Bit input mode options (only the SD Card type has the bit input)
- Tightly sealed structure that blocks water and dust with IP66 protection rating suitable for outdoor installation
- Cable entry : PG 13.5
- Materials : Horn-PC, Housing-PC+ABS
- Ambient operating temperature : -30°C to +50°C(Standard type)
 - -30°C to +50°C(SD Card type)
- Protection rating : IP66
- · Certificates : CE Compliant, UL
- · Compliant with RoHS directive

The input method of built-in sound type

ON OFF	1	2	3	4	5
No.					5
0	0	0	0	0	0
1	0	0	0	0	1
2	0	0	0	1	0
:	:	:	:	:	:
31	1	1	1	1	1

Select from 31 pre-recorded output sound options by using a combination of the 5 channel input switches.

The binary input method allows you to express each of the 31 alarm sound signals with a "0"or "1"by switching the 5 channels on and off as shown in the table.

Sound selection instruction for SD Card type

You can select between pre-recorded sound mode and SD Card sound (MP3) mode with the SOUND selection switch.



Selection between pre-recorded sound

mode and SD Card sound mode

0 : pre-recorded sound mode

1: SD Card sound mode

- 31 built-in alarm sounds and special sound
- Supports SD Cards for external sound (MP3)
- Binary Input : 31Ch
- Bit Input : 5Ch(SD Card only)
- A versatile product that can play MP3 files via the SD card
- For detailed setup instructions, please see Page 144 for the special beep-type products.
- Channel 1 is set as the factory default




(Units : mm)

QWH series

IP66	-30~+50°C	HORN	115 dB ° (((- ♪ °	123 dB ■ (((-)
SD mp3	113 dB (((-♪	118 dB (((-)		RoHS








QWH50 series

Sound Selection and Wiring Instructions

- Standard : Internal switch
- Customization : External contact(LC)



- Channel selection, 5 sounds available with Bit input and 31 sound available with Binary input
- DC type : Black line is negative(-)
- Please refer to Page 148 for channel input. (Wiring Instructions is changed to channel selection switches)

Wall Mount Electric Horn with Pre-recorded Special Warning Sound


QWH35 Wall Mount Electric Horn MP3(SD Card) with Pre-recorded Special Warning Sound

Model number	Voltage	Current	Binary input/ Channels	Certificates	Weight
QWH35	DC12V-24V	Max 0.930A	• Bit Input : 5Ch (SD Card)	CE	
Built-in standard sound	AC110V-220V	Max 0.300A	• Binary Input : 31Ch		0.9kg
QWH35SD	DC12V-24V	Max 0.980A	 Warning Sounds: Max.115dB MP3 Messages : Max.113dB 	UD DC only	1.0kg
MP3	AC110V-220V	Max 0.270A	Nil 5 Messages . Max. 1150D	DC Only	

* DC type model has a free-voltage range of 10V-30V.

* AC type model has a free-voltage range of 100V-240V.


Technical Diagram



QWH50 Wall Mount Electric Horn MP3(SD Card) with Pre-recorded Special Warning Sounds

Model number	Voltage	Current	Binary input/ Channels	Certificates	Weight
QWH50	DC12V-24V	Max. 3.480A	Bit Input : 5Ch (SD Card)	CE	
Built-in standard sound	AC110V-220V	Max. 0.460A	• Binary Input : 31Ch	-	2.7kg
QWH50SD MP3	DC12V-24V AC110V-220V	Max. 4.310A Max. 0.530A	Warning Sounds: Max.123dB MP3 Messages : Max.118dB	UC only	2.8kg
* AC type mor	lel has a free-v	oltage range	of 1001/-2401/		

* AC type model has a free-voltage range of 100V-240V



Customization

• External threading of sound selection signal line (Model number : -LC)

		440/000		
QWH50	-	110/220	-	LC
[Model number]		[Voltage]		[Sound selection]
I				I
• QWH35	• 12	2/24-DC12V-24V		 Standard
• QWH35SD	• 11	10/220-AC110V-220V		-Built-in Switch
• QWH50				• LC
• QWH50SD				-External contact