


FOOT MASTER®

Stainless steel casters SPM series









 180~400kg  RoHS  -10~90°C





Brackets: Pressed stainless steel plate, double ball bearing with hardened stainless steel bearing seats in the swivel head, strong welded frame, smooth side brake system, bolted wheel axle structure, completely corrosion-resistant components applied

Surface Treatment: Electrolytic polishing

* Recommended Load = Load Cap. × 3

Swivel	Rigid	Swivel with brake	Wheel type	 mm	 mm	 Kg	 mm	 mm	 mm	 mm	 mm
SPM-130-ASF	SPM-130-ARF	SPM-130-BSF	HRD	130	48	180	162	50	115x102	92x66 76x76	11
SPM-150-ASF	SPM-150-ARF	SPM-150-BSF		150	48	210					
SPM-130-ASF	SPM-130-ARF	SPM-130-BSF	MCD	130	48	400	162	50	115x102	92x66 76x76	11
SPM-150-ASF	SPM-150-ARF	SPM-150-BSF		150	48	400					

Options

						
Code Suffix	HRD	MCD				
Description	Rubber(A85)	MC nylon(D80)				
Available for	130 ~ 150	130 ~ 150				

Guide for selection of wheels : Stainless steel casters

Image	Series	Description	Wheel code	Wheel dia mm	Wheel width mm	Axle bore mm	Hub length mm	Load capacity Kg	Bearing type
	NYN	– Nylon 66(Shore D70) – No bearing	NYN-50-25	50	25	10	27	280	X
			NYN-63-30	63	30	12	34	550	X
	MCN	– MC nylon(Shore D80) – No bearing	MCN-49-25	49	25	10	27	280	X
			MCN-62-28	62	28	12	33	550	X
	MCD	– MC nylon(Shore D80) – Two stainless steel ball bearings	MCD-130-48	130	48	20	48	600	6204 ZZ
			MCD-150-48	150	48	20	48	600	6204 ZZ
	TUN	– Injected polyurethane (Shore A92) – PP core – No bearing	TUN-75-25	75	25	8	40	75	X
			TUN-100-30	100	30	8	40	100	X
			TUN-125-30	125	30	8	40	110	X
	TUSS	– Injected polyurethane (Shore A92) – PP core – One stainless steel ball bearing	TUSS-75-25	75	25	8	40	75	6202 ZZ
			TUSS-100-30	100	30	8	40	100	6202 ZZ
			TUSS-125-30	125	30	8	40	110	6202 ZZ
	TUD	– Injected polyurethane (Shore A92) – PP core – Two stainless steel ball bearings	TUD-100-30	100	30	8	30	100	608 ZZ
			TUD-125-30	125	30	8	30	110	608 ZZ
	HRN	– Injected rubber (Shore A85) – PP core – No bearing	HRN-75-25	75	25	8	40	75	X
			HRN-100-30	100	30	8	40	100	X
			HRN-125-30	125	30	8	40	110	X
	HRSS	– Injected rubber (Shore A85) – PP core – One stainless steel ball bearing	HRSS-75-25	75	25	8	40	75	6202 ZZ
			HRSS-100-30	100	30	8	40	100	6202 ZZ
			HRSS-125-30	125	30	8	40	110	6202 ZZ
	HRD	– Injected rubber (Shore A85) – PP core – Two stainless steel ball bearings	HRD-100-30	100	30	8	30	100	608 ZZ
			HRD-125-30	125	30	8	30	110	608 ZZ
			HRD-130-48	130	48	15	50	180	6202 ZZ
			HRD-150-48	150	48	15	50	210	6202 ZZ